
RAIL INFRASTRUCTURE REHABILITATION AT BALZANO MARINE TERMINAL FOR

SOUTH JERSEY PORT CORPORATION





VICINITY MAP

URBAN PROJECT NO. 2021500064.000

2021500064 000 - S.IPC Balzano Bail Rehah







~1	Sheet List Table
Sheet Number	Sheet Title
G-000	COVER SHEET
C 001	CIVIL NOTES AND LEGENDS
C-001 C-002	NOTES AND LEGENDS NOTES AND LEGENDS
C-101	EXISTING CONDITIONS 1
C-102	EXISTING CONDITIONS 2
C-103	EXISTING CONDITIONS 3
C-104	EXISTING CONDITIONS 4
C-105	EXISTING CONDITIONS 5
C-106	EXISTING CONDITIONS 6
C-201	PROPOSED STORM & WATER 1
C-202	PROPOSED STORM & WATER 2
C-203	PROPOSED STORM & WATER 3
C-204	PROPOSED STORM & WATER 4
C-205	PROPOSED STORM & WATER 5
C-206	PROPOSED STORM & WATER 6
C-301 C-302	PROPOSED GRADING 1 PROPOSED GRADING 2
C-302 C-303	PROPOSED GRADING 2 PROPOSED GRADING 3
C-303 C-304	PROPOSED GRADING 4
C-305	PROPOSED GRADING 5
C-306	PROPOSED GRADING 6
C-401	PROPOSED MATERIALS 1
C-402	PROPOSED MATERIALS 2
C-403	PROPOSED MATERIALS 3
C-404	PROPOSED MATERIALS 4
C-405	PROPOSED MATERIALS 5
C-406	PROPOSED MATERIALS 6
C-501	PROPOSED SITE DETAILS 1
C-502	PROPOSED SITE DETAILS 2
C-503	PROPOSED SITE DETAILS 3
S-001	STRUCTURAL GENERAL STRUCTURAL NOTES
S-101	LOADING DOCK PLAN AT SHED 1 - PLAN AND SECTION
S-102	CONC. FLOOR AT BUILDING A - PLAN, SECTION AND DETAIL
S-103	CANOPY FRAMING PLAN AT BUILDING A AND SECTIONS
S-104	LOADING DOCK DETAILS
	TRACKWORK
CP-1	CONSTRUCTION PHASING PLAN
G-02	GENERAL NOTES AND LEGEND
G-03	TRACKWORK GEOMETRY DEFINITIONS
G-04	DRAWING SHEET INDEX
T-1 T-2	PROPOSED TRACK CONSTRUCTION
	DDODOSED TDACK CONSTRUCTION
	PROPOSED TRACK CONSTRUCTION
T-3 T-4	PROPOSED TRACK CONSTRUCTION
T-4	
T-4 T-5	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION
T-4 T-5 T-6	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION
T-4 T-5 T-6 T-10	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION
T-4 T-5 T-6 T-10 T-13	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION HORIZONTAL TRACK GEOMETRY DATA
T-4 T-5 T-6 T-10 T-13 T-14	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION HORIZONTAL TRACK GEOMETRY DATA PROPOSED TOP OF RAIL PROFILES - 1 OF 2
T-4 T-5 T-6 T-10 T-13 T-14 T-20	PROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONHORIZONTAL TRACK GEOMETRY DATAPROPOSED TOP OF RAIL PROFILES - 1 OF 2PROPOSED TOP OF RAIL PROFILES - 2 OF 2
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22	PROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONHORIZONTAL TRACK GEOMETRY DATAPROPOSED TOP OF RAIL PROFILES - 1 OF 2PROPOSED TOP OF RAIL PROFILES - 2 OF 2TRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23	PROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONHORIZONTAL TRACK GEOMETRY DATAPROPOSED TOP OF RAIL PROFILES - 1 OF 2PROPOSED TOP OF RAIL PROFILES - 2 OF 2TRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-24	PROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONHORIZONTAL TRACK GEOMETRY DATAPROPOSED TOP OF RAIL PROFILES - 1 OF 2PROPOSED TOP OF RAIL PROFILES - 2 OF 2TRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-23 T-24 T-25	PROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONHORIZONTAL TRACK GEOMETRY DATAPROPOSED TOP OF RAIL PROFILES - 1 OF 2PROPOSED TOP OF RAIL PROFILES - 2 OF 2TRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-23 T-24 T-25	PROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONHORIZONTAL TRACK GEOMETRY DATAPROPOSED TOP OF RAIL PROFILES - 1 OF 2PROPOSED TOP OF RAIL PROFILES - 2 OF 2TRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILS
T-4	PROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONHORIZONTAL TRACK GEOMETRY DATAPROPOSED TOP OF RAIL PROFILES - 1 OF 2PROPOSED TOP OF RAIL PROFILES - 2 OF 2TRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILSMISC. TRACKWORK DETAILSMISC. TRACKWORK DETAILS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-23 T-24 T-25 T-26	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION HORIZONTAL TRACK GEOMETRY DATA PROPOSED TOP OF RAIL PROFILES - 1 OF 2 PROPOSED TOP OF RAIL PROFILES - 2 OF 2 TRACK CONSTRUCTION DETAILS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-23 T-24 T-25 T-26	PROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONPROPOSED TRACK CONSTRUCTIONHORIZONTAL TRACK GEOMETRY DATAPROPOSED TOP OF RAIL PROFILES - 1 OF 2PROPOSED TOP OF RAIL PROFILES - 2 OF 2TRACK CONSTRUCTION DETAILSTRACK CONSTRUCTION DETAILSMISC. TRACKWORK DETAILSMISC. TRACKWORK DETAILS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-23 T-24 T-25 T-26	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION HORIZONTAL TRACK GEOMETRY DATA PROPOSED TOP OF RAIL PROFILES - 1 OF 2 PROPOSED TOP OF RAIL PROFILES - 1 OF 2 PROPOSED TOP OF RAIL PROFILES - 2 OF 2 TRACK CONSTRUCTION DETAILS CONDUIT SCHEMATIC & ELECTRICAL DETAILS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-24 T-25 T-26 E-001	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION HORIZONTAL TRACK GEOMETRY DATA PROPOSED TOP OF RAIL PROFILES - 1 OF 2 PROPOSED TOP OF RAIL PROFILES - 2 OF 2 TRACK CONSTRUCTION DETAILS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-24 T-25 T-26 E-001	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION HORIZONTAL TRACK GEOMETRY DATA PROPOSED TOP OF RAIL PROFILES - 1 OF 2 PROPOSED TOP OF RAIL PROFILES - 2 OF 2 TRACK CONSTRUCTION DETAILS ELECTRICAL CONDUIT SCHEMATIC & ELECTRICAL DETAILS EXISTING BERTH NUMBERING & CROSS SECTION RECORD DRAWINGS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-24 T-25 T-26 E-001 EX-0	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION HORIZONTAL TRACK GEOMETRY DATA PROPOSED TOP OF RAIL PROFILES - 1 OF 2 PROPOSED TOP OF RAIL PROFILES - 2 OF 2 TRACK CONSTRUCTION DETAILS ELECTRICAL ELECTRICAL ELECTRICAL EXISTING RECORD DRAWINGS EXISTING BERTH NUMBERING & CROSS SECTION RECORD DRAWINGS BERTH 3 - BERTH 4 RAIL CONNECTIONS CONSTRUCTION
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-24 T-25 T-26 E-001 EX-0 EX-1	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION HORIZONTAL TRACK GEOMETRY DATA PROPOSED TOP OF RAIL PROFILES - 1 OF 2 PROPOSED TOP OF RAIL PROFILES - 2 OF 2 TRACK CONSTRUCTION DETAILS DELECTRICAL ELECTRICAL EXISTING RECORD DRAWINGS EXISTING BERTH NUMBERING & CROSS SECTION RECORD DRAWINGS
T-4 T-5 T-6 T-10 T-13 T-14 T-20 T-21 T-22 T-23 T-24 T-25 T-26 E-001 EX-0	PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION PROPOSED TRACK CONSTRUCTION HORIZONTAL TRACK GEOMETRY DATA PROPOSED TOP OF RAIL PROFILES - 1 OF 2 PROPOSED TOP OF RAIL PROFILES - 2 OF 2 TRACK CONSTRUCTION DETAILS MISC. TRACKWORK DETAILS ELECTRICAL CONDUIT SCHEMATIC & ELECTRICAL DETAILS EXISTING RECORD DRAWINGS EXISTING BERTH NUMBERING & CROSS SECTION RECORD DRAWINGS BERTH 3 - BERTH 4 RAIL CONNECTIONS CONSTRUCTION RECORD DRAWINGS

	JERSEY PORT CORP. BALZANO BLVD, CAMDEN, NJ 08103 TEL.: (856) 757-4969	ISSUED FOR BID
		AN ENGINEERS, INC. 530 Walnut Street Philadelphia, PA 19106 922-8080 Fax (215) 922-8082
KC 00°EL W 70°	CAMDE	EN, NJ
C C C C C C C C C C C C C C C C C C C	RAIL INFRASTRUCT	MARINE TERMINAL URE REHABILITATION R SHEET
and Sona L Entrut	DWN FYC PROJ#2021500064.000	DRAWING NUMBER
—	CHK MGW DATE 06/24/2022	G-000

GENERAL NOTES:

- DESIGN AND CONSTRUCTION SHALL COMPLY WITH ALL APPLICABLE STATE AND LOCAL CODES AND STANDARDS, THE PROJECT SPECIFICATIONS, AND DRAWINGS. NOTES ON DRAWINGS SHALL TAKE PRECEDENCE OVER PROJECT SPECIFICATIONS. SPECIFIC NOTES ON DETAIL DRAWINGS TAKE PRECEDENCE OVER GENERAL NOTE DRAWINGS. STATE AND LOCAL CODES SHALL TAKE PRECEDENCE OVER PROJECT SPECIFICATIONS AND NOTES ON DRAWINGS.
- THE CONTRACTOR SHALL FIELD VERIFY ALL DIMENSIONS AND EXISTING CONDITIONS PRIOR TO MOBILIZING. ALL EXISTING & PROPOSED DIMENSIONS AND ELEVATIONS SHOWN ON THE DRAWINGS SHALL BE VERIFIED BY THE CONTRACTOR PRIOR TO ANY FABRICATION OR ERECTION. NOTIFY THE ENGINEER OF ANY DISCREPANCIES IMMEDIATELY.
- THE CONTRACTOR SHALL REMOVE FROM THE SITE ALL WASTE MATERIAL, DEMOLISHED MATERIAL AND DEBRIS GENERATED DURING THE COURSE OF THE WORK, U.N.O. DISPOSAL OF ALL GENERATED WASTE MATERIAL, DEMOLISHED MATERIAL AND DEBRIS IS THE CONTRACTOR'S RESPONSIBILITY. DISPOSE OF ALL MATERIAL IN ACCORDANCE WITH APPLICABLE FEDERAL, STATE AND LOCAL RULES AND REGULATIONS.
- THE CONTRACTOR SHALL ABIDE BY ALL APPLICABLE ENVIRONMENTAL PROTECTION STANDARDS, CODES, LAWS, REGULATIONS, AND PERMITS.
- THE CONTRACTOR SHALL CONDUCT HIS OPERATIONS SO AS TO NOT INTERFERE WITH, OR BE DETRIMENTAL TO, VESSEL AND VEHICULAR TRAFFIC DURING THE COURSE OF THE WORK.
- ALL STRUCTURES ARE DESIGNED TO BE SELF-SUPPORTING AND STABLE AFTER ERECTION IS FULLY COMPLETE. IT IS THE RESPONSIBILITY OF THE CONTRACTOR TO DETERMINE ERECTION PROCEDURES AND SEQUENCE AND TO ENSURE THE SAFETY OF THE STRUCTURE AND ITS COMPONENT PARTS DURING ERECTION. THIS INCLUDES THE ADDITION OF WHATEVER SHORING, SHEETING, TEMPORARY BRACING, GUYS OR TIE DOWNS THAT MAY BE NECESSARY. SUCH MATERIAL SHALL REMAIN THE CONTRACTOR'S PROPERTY AFTER COMPLETION OF THE PROJECT.
- THE CONTRACTOR SHALL FOLLOW ALL APPLICABLE SAFETY CODES AND REGULATIONS DURING ALL PHASES OF CONSTRUCTION.
- DESIGN AND CONSTRUCTION SHALL COMPLY WITH ALL APPLICABLE STATE AND LOCAL CODES AND STANDARDS, PROJECT SPECIFICATIONS AND DRAWINGS.
- EXISTING TOPOGRAPHIC FEATURES, GRADE CONTOURS, PROPERTY AND RIGHT-OF-WAY LINES SHOWN WERE TAKEN FROM A PLAN ENTITLED "BOUNDARY AND TOPOGRAPHIC SURVEY FOR BALZANO MARINE TERMINAL PORT OF CAMDEN" PREPARED BY COLLIERS ENGINEERING & DESIGN DATED MAY 10TH, 2022.
- 10. THE UNDERGROUND UTILITIES SHOWN HAVE BEEN LOCATED FROM FIELD SURVEY INFORMATION AND EXISTING DRAWINGS. THE SURVEYOR MAKES NO GUARANTEES THAT THE UNDERGROUND UTILITIES SHOWN COMPRISE ALL SUCH UTILITIES IN THE AREA, EITHER IN SERVICE OR ABANDONED. THE SURVEYOR FURTHER DOES NOT WARRANT THAT THE UNDERGROUND UTILITIES SHOWN ARE IN THE EXACT LOCATION INDICATED.
- 11. HORIZONTAL DATUM IS BASED ON N.J.S.P.C.S NAD'83. VERTICAL DATUM IS BASED ON NAVD 1988.
- 12. THE CONTRACTOR IS REQUIRED TO NOTIFY THE NEW JERSEY ONE CALL SYSTEM AT 1-800-272-1000 NOT LESS THAN THREE (3) FULL WORKING DAYS PRIOR TO ANY EXCAVATION.
- 13. THE PROPERTY IS LOCATED WITHIN AN AREA HAVING THE FLOOD ZONE DESIGNATION OF ZONE X ON FLOOD INSURANCE MAP ENTITLED "PANEL 0062E, FIRM, FLOOD INSURANCE RATE MAP, CAMDEN COUNTY, NEW JERSEY (ALL JURISDICTIONS), PANEL 62 OF 305" MAP NUMBER 34007C0062E, EFFECTIVE DATE SEPTEMBER 28, 2007.
- 14. CONTRACTOR TO ACCOUNT FOR TIDAL WATERS ON SITE DURING CONSTRUCTION. INLETS MAY SURCHARGE ONTO SITE DURING HIGH TIDE.
- 15. THIS DRAWING WAS MADE WITHOUT THE BENEFIT OF A TITLE REPORT.
- 16. THE CONTRACTOR SHALL SCHEDULE AND CONDUCT ALL CONSTRUCTION TO MINIMIZE EROSION.
- 17. APPROVED EROSION AND SEDIMENTATION CONTROL MEASURES SHALL BE PROVIDED AND MAINTAINED UNTIL ALL WORK IS COMPLETED. E&S PLANS SHALL BE AVAILABLE ON SITE UNTIL CONSTRUCTION IS COMPLETED. THE CONTRACTOR SHALL CONDUCT OPERATIONS TO COMPLY WITH THE APPROVED EROSION AND SEDIMENTATION CONTROL PLAN. IF THE APPROVED PLAN(S) CANNOT BE FOLLOWED, THE CONTRACTOR SHALL OBTAIN WRITTEN APPROVAL OF ALTERNATIVE EROSION AND SEDIMENTATION CONTROLS BY THE APPROPRIATE REGULATORY AGENCY. AT NO TIME SHALL WATER CONTAINING SEDIMENTS OR POLLUTANTS BE DISCHARGED INTO DRAINAGE DITCHES, STORMWATER PIPES OR WATERCOURSES.
- 18. THE CONTRACTOR IS REQUIRED TO PROVIDE ADEQUATE SHEETING, SHORING AND DEWATERING IN ALL TRENCHES AND EXCAVATIONS AS NECESSARY IN ACCORDANCE WITH OSHA: AND IS SOLELY RESPONSIBLE FOR THE SAFETY OF SHEETING, SHORING AND DEWATERING.
- 19. THE CONTRACTOR SHALL REMOVE TREES THAT WILL INTERFERE WITH PROPOSED WORK INCLUDING STUMPS THAT ARE WITHIN THE LIMITS OF CONSTRUCTION. BEFORE REMOVAL OF ANYTHING NOT MARKED FOR REMOVAL ON THE PLANS, OBTAIN APPROVAL FROM THE OWNER.
- 20. CLEAR AND GRUB ALL VEGETATION AND OTHER MISCELLANEOUS ITEMS WITHIN THE LIMITS OF WORK PRIOR TO ANY EARTHMOVING ACTIVITIES.
- 21. IF DISCREPANCIES IN OR OMISSIONS FROM THE CONTRACT DOCUMENTS ARE FOUND, NOTIFY THE ENGINEER IN WRITING IMMEDIATELY. NO CONSIDERATION OR ALLOWANCES WILL BE GRANTED FOR ANY ALLEGED MISUNDERSTANDING OF MATERIAL TO BE FURNISHED OR WORK TO BE PERFORMED.

UTILITY NOTES:

- 1. THE LOCATION OF UNDERGROUND UTILITIES IS TAKEN FROM OWNER RECORDS AND FIELD LOCATION OF VENTS, VALVES, MANHOLES, INLETS, ETC. THE EXTENT AND EXACT LOCATION AND DEPTH OF UNDERGROUND UTILITIES HAS NOT BEEN VERIFIED BY THE OWNER OR ITS REPRESENTATIVE. THE CONTRACTOR SHALL DETERMINE THE EXTENT AND EXACT LOCATION AND DEPTH OF ALL EXISTING PRIVATE AND PUBLIC UTILITIES PRIOR TO COMMENCING WORK. THE CONTRACTOR SHALL BE FULLY RESPONSIBLE FOR ANY AND ALL DAMAGES WHICH MIGHT BE OCCASIONED BY THE CONTRACTOR'S FAILURE TO EXACTLY LOCATE AND PRESERVE ANY AND ALL UNDERGROUND UTILITIES.
- 2. THE CONTRACTOR IS REQUIRED TO NOTIFY THE NEW JERSEY ONE CALL SYSTEM AT 1-800-272-1000 NOT LESS THAN THREE (3) FULL WORKING DAYS PRIOR TO ANY EXCAVATION, AND SHALL PROVIDE WRITTEN NOTICE TO THE OWNER THAT CONTACT HAS BEEN MADE. UTILITIES LOCATED WITHIN THE PROJECT MAY BE PRIVATE AND MAY NOT BE LOCATED BY THE ONE CALL SERVICES. THEREFORE THE CONTRACTOR SHALL BE RESPONSIBLE TO LOCATE THOSE UTILITIES.
- 3. CAUTION: HIGH VOLTAGE LINES MAY EXIST WITHIN THE PROJECT LIMITS. ALL WORK IS TO BE PERFORMED IN CONFORMITY WITH ALL STATE, FEDERAL, UTILITY AND CONTRACT REQUIREMENTS. URBAN ENGINEERS INC. AND THE OWNER HAVE NO CONTROL OVER THE MEANS, METHODS, CHOICE OF EQUIPMENT, SEQUENCING OF AND SAFETY PRACTICES USED OR NOT USED, IN, ON OR AROUND HIGH VOLTAGE LINES OR OTHER UTILITY STRUCTURES, AS THESE ITEMS ARE THE RESPONSIBILITY OF THE PARTIES PHYSICALLY PERFORMING OR CONTROLLING, THE PERFORMANCE OF THE WORK. EXCEPT WHERE ELECTRICAL DISTRIBUTION AND TRANSMISSION LINES HAVE BEEN DEENERGIZED AND VISIBLY DE-ENERGIZED GROUNDED AT THE POINT OF WORK, ASSUME THAT ALL SUCH LINES ARE ENERGIZED AND CONFORM OPERATIONS TO INTER ALIA, TITLE 29 OF THE CODE OF FEDERAL REGULATIONS, SECTION 1926.550(a)(19).
- 4. THE CONTRACTOR SHALL NOTIFY THE OWNER IN ADVANCE FOR ANY WATER SHUT-OFF. NO WATER SHUT-OFF WILL BE ALLOWED UNLESS APPROVAL FROM THE OWNER IS OBTAINED.
- 5. THE CONTRACTOR SHALL PROTECT AND MAINTAIN ALL EXISTING UTILITIES AND/OR TEMPORARILY RELOCATE AND PROPERLY SUPPORT EXISTING UTILITIES AS NECESSARY.
- 6. THE CONTRACTOR SHALL PROVIDE NECESSARY MATERIAL, EQUIPMENT AND MANPOWER IN ORDER TO RESTORE INTERRUPTED OR DAMAGED UTILITY SERVICES 24 HOURS PER DAY UNTIL UTILITY SERVICES HAVE BEEN COMPLETELY RESTORED OR TEMPORARY SERVICES HAVE BEEN DETERMINED SUFFICIENT BY THE ENGINEER.
- 7. THE CONTRACTOR SHALL OBTAIN FROM THE APPROPRIATE UTILITY COMPANY OR CITY DEPARTMENT, VERIFICATION OF THE CURRENT STATUS OF UTILITIES AND STRUCTURES SHOWN ON THE CONTRACT DOCUMENTS PRIOR TO WORKING ON OR NEAR SUCH STRUCTURES AND UTILITIES.

REV	BY	DATE	DESCRIPTION

EXISTING LEGEND

XISTING LEGEND						
<i>5</i>	MAJOR CONTOUR					
— — -4 — — -	MINOR CONTOUR					
	EXISTING BUILDING OUTLINE					
xxx	EXISTING FENCE					
	EXISTING OVERHEAD ELECTRIC LINE					
	EXISTING STORM LINE					
	EXISTING SANITARY SEWER LINE					
<i>FW</i>	EXISTING FIRE WATER LINE					
w	EXISTING WATER LINE					
-0-	EXISTING UTILITY POLE					
ЪС.	EXISTING FIRE HYDRANT					
\bigcirc	EXISTING MANHOLE					
CB	EXISTING STORM INLET					
o ^{DS}	EXISTING DOWNSPOUT					

PROPOSED LEGEND

5.0
4.5
ST
FW

MAJOR CONTOUR MINOR CONTOUR PROPOSED STORMWATER LINE PROPOSED FIREWATER LINE

FH
ewv
o ^B
۵ ک ۵

EXISTING UTILITY TO BE REMOVED OR ABANDONED PROPOSED STORMWATER INLET PROPOSED TRACK DRAIN PROPOSED FIRE HYDRANT PROPOSED WATER VALVE PROPOSED BOLLARD PROPOSED FLOW ARROW PROPOSED CONCRETE PROPOSED ASPHALT

ISSUED FOR BID

Philadelphia, PA 19106 (215) 922-8080 Fax (215) 922-8082



CAMDEN, NJ SJPC BALZANO MARINE TERMINAL RAIL INFRASTRUCTURE REHABILITATION NOTES AND LEGENDS

JRBAN URBAN ENGINEERS, INC.

^{WN} GJB PROJ # 2021500064.000 AWING NUMBER CHK M.IT DATE 06/24/2022

ENGINEERS

C-001

CAMDEN COUNTY SOIL EROSION AND SEDIMENT CONTROL NOTES

- ALL APPLICABLE EROSION AND SEDIMENT CONTROL PRACTICES SHALL BE IN PLACE PRIOR TO ANY GRADING OPERATION AND/OR INSTALLATION OF PROPOSED STRUCTURES OR UTILITIES.
- SOIL EROSION AND SEDIMENT CONTROL PRACTICES ON THIS PLAN SHALL BE CONSTRUCTED IN ACCORDANCE WITH THE STANDARDS FOR SOIL EROSION AND SEDIMENT CONTROL IN NEW JERSEY.
- APPLICABLE EROSION AND SEDIMENT CONTROL PRACTICES SHALL BE LEFT IN PLACE UNTIL CONSTRUCTION IS COMPLETED AND/OR THE AREA IS STABILIZED.
- THE CONTRACTOR SHALL PERFORM ALL WORK, FURNISH ALL MATERIALS AND INSTALL ALL MEASURES REQUIRED TO REASONABLY CONTROL SOIL EROSION RESULTING FROM CONSTRUCTION OPERATIONS AND PREVENT EXCESSIVE FLOW OF SEDIMENT FROM THE CONSTRUCTION SITE.
- ANY DISTURBED AREA THAT IS TO BE LEFT EXPOSED FOR MORE THAN THIRTY (30) DAYS AND NOT SUBJECT TO CONSTRUCTION TRAFFIC SHALL IMMEDIATELY RECEIVE A TEMPORARY SEEDING AND FERTILIZATION IN ACCORDANCE WITH THE NEW JERSEY STANDARDS AND THEIR RATES SHOULD BE INCLUDED IN THE NARRATIVE. IF THE SEASON PROHIBITS TEMPORARY SEEDING, THE DISTURBED AREAS WILL BE MULCHED WITH SALT HAY OR EQUIVALENT AND ANCHORED IN ACCORDANCE WITH THE NEW JERSEY STANDARDS (I.E. PEG AND TWINE, MULCH NETTING OR LIQUID MULCH BINDER).
- IT SHALL BE THE RESPONSIBILITY OF THE DEVELOPER TO PROVIDE CONFIRMATION OF LIME, FERTILIZER AND SEED APPLICATION AND RATES OF APPLICATION AT THE REQUEST OF THE CAMDEN COUNTY SOIL CONSERVATION DISTRICT.
- ALL CRITICAL AREAS SUBJECT TO EROSION WILL RECEIVE A TEMPORARY SEEDING IN COMBINATION WITH STRAW MULCH AT A RATE OF 2 TONS PER ACRE, ACCORDING TO THE NEW JERSEY STANDARDS IMMEDIATELY FOLLOWING ROUGH GRADING.
- THE SITE SHALL AT ALL TIMES BE GRADED AND MAINTAINED SUCH THAT ALL STORMWATER RUNOFF IS DIVERTED TO SOIL EROSION AND SEDIMENT CONTROL FACILITIES.
- ALL SEDIMENTATION STRUCTURES WILL BE INSPECTED AND MAINTAINED ON A REGULAR BASIS AND AFTER EVERY STORM EVENT.
- 10. A CRUSHED STONE, TIRE CLEANING PAD WILL BE INSTALLED WHEREVER A CONSTRUCTION ACCESS EXISTS. THE STABILIZED PAD WILL BE INSTALLED ACCORDING TO THE STANDARD FOR STABILIZED CONSTRUCTION ACCESS
- 11. ALL DRIVEWAYS MUST BE STABILIZED WITH 2 1/2" CRUSHED STONE OR SUBBASE PRIOR TO INDIVIDUAL LOT CONSTRUCTION.
- 12. PAVED ROADWAYS MUST BE KEPT CLEAN AT ALL TIMES.

X:\2021500064.000 - S.IPC Balzano Rail Rehab\Technical\Civil\DWG\Sheets\SHT-C000-GENERAL.dwg

- 13. ALL CATCH BASIN INLETS WILL BE PROTECTED ACCORDING TO THE CERTIFIED PLAN.
- 14. ALL DEWATERING OPERATIONS MUST DISCHARGE DIRECTLY INTO A SEDIMENT FILTER AREA. THE SEDIMENT FILTER SHOULD BE COMPOSED OF A SUITABLE SEDIMENT FILTER FABRIC.
- 15. OFFSITE SEDIMENT DISTURBANCE MAY REQUIRE ADDITIONAL CONTROL MEASURES TO BE DETERMINED BY THE EROSION CONTROL INSPECTOR.
- 16. ANY CONVEYANCE OF THIS PROJECT PRIOR TO ITS COMPLETION WILL TRANSFER FULL RESPONSIBILITY FOR COMPLIANCE WITH THE CERTIFIED PLAN TO ANY SUBSEQUENT OWNERS.
- 17. METHODS FOR THE MANAGEMENT OF HIGH ACID PRODUCING SOILS SHALL BE IN ACCORDANCE WITH THE STANDARDS. HIGH ACID PRODUCING SOILS ARE THOSE FOUND TO CONTAIN IRON SULFIDES OR HAVE A pH OF 4 OR LESS.
- 18. TEMPORARY AND PERMANENT SEEDING MEASURES MUST BE APPLIED ACCORDING TO THE NEW JERSEY STANDARDS, AND MULCHED WITH SALT HAY OR EQUIVALENT AND ANCHORED IN ACCORDANCE WITH THE NEW JERSEY STANDARDS (I.E. PEG AND TWINE, MULCH NETTING OR LIQUID MULCH BINDER).
- 19. MAXIMUM SIDE SLOPES OF ALL EXPOSED SURFACES SHALL NOT BE CONSTRUCTED STEEPER THAN 3:1 UNLESS OTHERWISE APPROVED BY THE DISTRICT.
- 20. DUST IS TO BE CONTROLLED BY AN APPROVED METHOD ACCORDING TO THE NEW JERSEY STANDARDS AND MAY INCLUDE WATERING WITH A SOLUTION OF CALCIUM CHLORIDE AND WATER.
- 21. ADJOINING PROPERTIES SHALL BE PROTECTED FROM EXCAVATION AND FILLING OPERATIONS ON THE PROPOSED SITE.
- 22. USE STAGED CONSTRUCTION METHODS TO MINIMIZE EXPOSED SURFACES, WHERE APPLICABLE.
- 23. ALL VEGETATIVE MATERIAL SHALL BE SELECTED IN ACCORDANCE WITH AMERICAN STANDARDS FOR NURSERY STOCK OF THE AMERICAN ASSOCIATION OF THE NURSERYMEN AND IN ACCORDANCE WITH THE NEW JERSEY STANDARDS.
- 24. THE SOIL EROSION INSPECTOR MAY REQUIRE ADDITIONAL SOIL EROSION MEASURES TO BE INSTALLED. AS DIRECTED BY THE DISTRICT INSPECTOR.

MAINTENANCE PROGRAM FOR SEDIMENT AND EROSION CONTROL:

THE CONTRACTOR IS RESPONSIBLE FOR MAINTAINING ALL EROSION CONTROL FACILITIES DURING CONSTRUCTION. ALL DAMAGED FACILITIES WILL BE REPAIRED WITHIN 24 HOURS. THE CONTRACTOR WILL NOT REMOVE ANY CONTROL FACILITY UNTIL DIRECTED BY THE ENGINEER. MATERIALS USED FOR EROSION CONTROL WILL BE DISPOSED OF OFF-SITE WHEN REMOVED. SUCH MATERIALS ARE CONSIDERED PROPERTY OF THE CONTRACTOR.

STABILIZED CONSTRUCTION ENTRANCE:

- COMPOST FILTER SOCK:
- AND AFTER ALL PRECIPITATION EVENTS. ANY NECESSARY REPAIRS WILL BE MADE IMMEDIATELY.
- 2. ACCUMULATED SEDIMENTS SHALL BE REMOVED AS REQUIRED TO KEEP THE SOCK FUNCTIONAL. IN ALL
- 3. ALL UNDERCUTTING OR EROSION OF THE TOE ANCHOR WILL BE REPAIRED IMMEDIATELY WITH COMPACTED BACKFILL MATERIALS.

SOIL STOCKPILES:

- 1. INSPECT SOIL STOCKPILES MONTHLY.
- 2. RESEED TO ESTABLISH GRASS COVER.
- SEEDING AND MULCHING OF DISTURBED AREAS AND NEW SLOPES:
- 1. FOLLOW TEMPORARY AND PERMANENT SEEDING SPECIFICATION GUIDELINES.
- COVER.

PUMPED WATER FILTER BAG:

- PUMPED WATER FILTERS SHALL BE INSPECTED WEEKLY AND AFTER EACH RAIN EVENT.
- OTHER DEBRIS WHICH COULD IMPAIR THE FUNCTION OF THE FILTER.

1. THE STRUCTURE'S THICKNESS WILL BE CONSTANTLY MAINTAINED TO THE SPECIFIED DIMENSIONS BY ADDING ROCK. A STOCKPILE OF ROCK MATERIAL WILL BE MAINTAINED ON THE SITE FOR THIS PURPOSE.

2. AT THE END OF EACH CONSTRUCTION DAY, ALL SEDIMENT DEPOSITED ON PUBLIC ROADWAYS WILL BE REMOVED BY USE OF A VACUUM TYPE ROAD SWEEPER AND RETURNED TO THE CONSTRUCTION SITE.

1. THE LOG INSTALLATION SHALL BE INSPECTED WEEKLY, BEFORE ANY ANTICIPATED PRECIPITATION EVENT,

CASES REMOVE DEPOSITS WHERE ACCUMULATIONS REACH 1/2 THE ABOVE-GROUND HEIGHT OF THE LOG.

2. DISTURBED AREAS AND NEW SLOPES SHALL BE INSPECTED WEEKLY AND AFTER EVERY RAIN EVENT.


3. MISSING MULCH SHALL BE REPLACED. RESEED AND MULCH UNTIL THE ESTABLISHMENT OF GOOD GRASS

2. SEDIMENT SHALL BE REMOVED WHEN IT REACHES THE CLEAN-OUT LEVEL ON THE MARKER AND REMOVE


REV	BY	DATE	DESCRIPTION


CIVIL/STRUCTURAL ABBREVIATIONS


ACI AMERICAN CONCRETE INSTITUTE LB POUND ASC AMERICAN INSTITUTE OF NS NEAR SIDE ALT ALTERNATE LG LONG LEG VERTICAL ANSI AMERICAN NATIONAL M METERS STANDARDS INSTITUTE mm MILLIMETERS APPROXIMATE MAX MAZIMUM APPROXIMATE MAX APPROXIMATE MAX APPROXIMATE MAX MAZIMUM APPROXIMATE MAX MAZIMUM APPROXIMATE MAX APPROXIMATE MAX APPROXIMATE MAX APPROXIMATE MAX APPROXIMATE MAX ADIT </th <th></th> <th></th>		
ASC * AMERICAN INSTITUTE OF NS = NEAR SIDE STANDARDS INSTITUTE LG LONG ANSI = AMERICAN NATIONAL M = METERS STANDARDS INSTITUTE mm MILLIMETERS APPROXIMATE MAX = MARSURD AST = AMERICAN SOCIETY OF MEA = MEASURED TESTING AND MATERIALS MH = MARNUM AWS = AMERICAN WELDING SOCIETY MHW = MEAN HIGH WATER BJD.P = DOTTOM OF PIPE MHW = MEAN HIGH WATER BJS = BACK TO BACK MIN = MINIMUM BG = BOTTOM OF CUBB MISCEL MEAN HIGH WATER BW = BOTTOM OF CUBB MISCEL MEAN HIGH WATER BW = BOTTOM OF CUBB MISCEL MEAN HIGH WATER BW = BOTTOM OF CUBB MISC MEAN HIGH WATER BW = BOTTOM OF CUBB MISC MEAN HIGH WATER BW = BOTTOM OF CUBB MISC MEAN HIGH WATER BW = BOTTOM OF CUBB MISC MEAN HIGH WATER CC = CHARNEL MPa MELDARCALS CIC = CONSTRUCTION JOINT NIC = NORTH CL = CONSTRUCTION JOINT NIC = NORTH </td <td>ACI = AMERICAN CONCRETE INSTITUTE</td> <td>LB = POUND</td>	ACI = AMERICAN CONCRETE INSTITUTE	LB = POUND
STEEL CONSTRUCTIONLFELINEAR FEETALTALTERNATELG> LONGALTALTERNATELG> LONGANS- AMERICAN NATIONALMMETERSSTANDARDS INSTITUTEMAXMAXIMUMASTM- AMERICAN SOCIETY OFMAA> MAXEMUMASTM- AMERICAN SOCIETY OFMAA> MAXEMUMASTM- AMERICAN WELDING SOCIETYMHHMANHOLEAWS- AMERICAN WELDING SOCIETYMHWMANHOLEBWBACK TO BACKMINMINMUMBC- BOTTOM OF URBMISC- MISCELLANEOUSBT- BOTTOM OF URBMISC- MISCELLANEOUSBW- BOTTOM OF WALLMLWMEAN LOWENELOW WATERBW- BOTTOM OF WALLMLW- MEAN NOW WATERBW- BOTTOM OF WALLMLW- MEAN PACALOWCC- CENTER TO CENTERMPH- MILES PER HOURCF- CUBIC FEETMSL- MECAPASCALSCVC- CONSTRUCTION JOINTNIC- NOT IN CONTRACTCJ- CONSTRUCTION JOINTNIC- NOT NO SCALECON- CONSTRUCTIONP/C- POLYVIN/LCHLORIDECONT- CONSTRUCTIONP/C- POLYVIN/LCHLORIDECONT- CONSTRUCTIONP/C- POLYVIN/LCHLORIDECONT- CONSTRUCTIONP/C- POLYVIN/LCHLORIDECONT- CONSTRUCTIONR/C- REINFORCED CONCRETE PIPEDR- DOWN RIVERR/CP- REINFORCED CONCRETE PIPEDR- DOWN RIVE	ACD = ADMIRALTY CHART DATUM	LLV = LONG LEG VERTICAL
ALT = ALTERNATE LG = LONG ANSI = AMERICAN SOCIETY MM = MERICS STANDARDS INSTITUTE mm MMLLIMETERS APPROXIMATE MAX = MARSURED TESTING AND MATERIALS MLA = MEASURED AWS = AMERICAN SOCIETY OF MEA = MEASURED AWS = AMERICAN SOCIETY OF MEA = MEASURED BUD = BOTTOM OF PIPE MHW = MEAN HIGH WATER BUP = BOTTOM OF QUBS MLLW = MESCLANEOUS BUT = BACK TO BACK MIN = MINUM = MEGAPASCALS C = CHANNEL MPa = MEGAPASCALS CIC = CHANNEL MPa = MEASUREDOUNC CIC = CHANNEL MPa = MEASPASCALS CIC = CONSTR	AISC = AMERICAN INSTITUTE OF	NS = NEAR SIDE
ANSI = AMERICAN NATIONAL M = METERS STANDARDS INSTITUTE mm = MILLIMETERS ARST = AMERICAN SOCIETY OF MAX = MAX ASTM = AMERICAN SOCIETY OF MAX = MAX BOD = BOTTOM OF PIPE MHW = MACH TOH MATER BLO,P. = BOTTOM OF PIPE MHW = MACH TOH OF PIPE BT = BACK TO BACK MIN = MINIMUM BC = BOTTOM OF CURB MISC = MISCELLANEOUS BT = BOTTOM OF FUEL MLW = MEAN HOR WATER BW = BOTTOM OF FUEL MLW = MEAN LOW WATER BW = BOTTOM OF FUEL MLW = MEAN LOW WATER BW = BOTTOM OF FUEL MLW = MEAN ELOW WATER BW = BOTTOM OF FUEL MLW = MEAN ACOUS CC = CHNREL MPH = MILLS PER HOUR CT = CONSTRUCTION JOINT NIC = NOT TO SCALE CD = CLEAR NT = NOT TO SCALE CONS = CONSTRUCTION PCC = NOT TO SCALE CONS = CONSTRUCTION PCC = POLYNIVL CHLORIDE CONT = CONSTRUCTION PCC = NOT TO SCALE CONS = CONSTRUCTION RCD = REINF	STEEL CONSTRUCTION	LF = LINEAR FEET
STANDARDS INSTITUTEmm# INLLIMETERSAPPROXEAMERICAN SOCIETY OFMAX# MEASUREDTESTING AND MATERIALSMH# MANHOLEBC.P.= BOTTOM OF PIPEMHWMEAN HIGHER HIGH WATERBC.P.= BOTTOM OF PIPEMHWMEAN HIGHER HIGH WATERBC.P.= BOTTOM OF CURBMISC= MISCELLANEOUSBC.T.= BOTTOM OF CURBMISC= MISCELLANEOUSBT.= BITUMINOUSMILW= MEAN LOWER LOW WATERBW= BOTTOM OF WALLMUWMEAN LOW WATERC= CHANNELMUW= MEAN LOWER LOW WATERC= CONTER TO CENTERMPA= MIESP ERHOURCF= CUBIC FEETMSL= MIESP ERHOURCF= CONSTRUCTION JOINTNC= NOTTO SCALECONST= CONSTRUCTION JOINTNC= NOTTO SCALECONT= CONSTRUCTIONNTS= NOTTO SCALECONT= CONSTRUCTIONRF= REINFORCED CONCRETE PIPECONT= CONSTRUCTIONRF= REINFORCED CONCRETE PIPEDC= DEPTHRC.P.= REINFORCED CONCRETE PIPEDC= DEPTHRC.P.= SANTARYDETI'S= DETAILSSCH= SANTARYDETI'S= DETAILSSCH= SANTARYDETI'S= DETAILSSCH= SANTARYDETI'S= DETAILSSCH= SANTARYDETI'S= DETAILSSCH= SANTARYDETI'S= DETAILSSCH= SANTARYDETI'S= DETAILSSCH <td>ALT = ALTERNATE</td> <td>LG = LONG</td>	ALT = ALTERNATE	LG = LONG
APPROXEAPPROXIMATEMAX= MAXINUMASTM= AMERICAN SOCIETY OFMEAMEAMEASUREDTESTING AND MATERALSMHMANHOLE IGH WATERAWS= AMERICAN WELDING SOCIETYMHWMEAN HIGHER HIGH WATERBUB= BACK TO BACKMIN= MINIMUMBC= BOTTOM OF PIPEMHWMEAN HIGHER HIGH WATERBW= BOTTOM OF OLRBMISC= MISCELLANEOUSBW= BOTTOM OF WALLMLWMEAN HIGHER HIGH WATERC= CHANNELMPWMEAN HORE LOW WATERCU= CHANNELMPH= MILES PER HOURCF= CUBIC FEETMSL= MEGAPASCALSC/C= CONSTRUCTION JOINTNICNORTHCJ= CONSTRUCTION JOINTNICNOT NO CONTRACTCLR= CLEARNTSSOT TO SCALECONC= CONSTRUCTIONPVCPOLYINYL CHLORIDECONT= CONSTRUCTIONPVCPOLYUNYL CHLORIDECONT= CONSTRUCTIONPVCPOLYUNYL CHLORIDEDT= DEPTHR.C.P.REMORGCINGDC= DEORSSOUTHDEG= DEGREESSANSANTARYDEG= DEGREESSANSANTARYDET= DISTANCESIMSMILARDIST= DISTANCESIMSMILARDIST= DISTANCESIMSMILARDIST= DISTANCESIMSMILARDIST= DISTANCESIMSMILARDIST= DISTANCESIMSMI	ANSI = AMERICAN NATIONAL	M = METERS
ASTM = AMERICAN SOCIETY OF MEA = MAEASURED TESTING AND MATERIALS MH = MANHOLE RVS = AMERICAN VELONG SOCIETY MHIW MEAN HIGHER HIGH WATER B.O.P. = BOTTOM OF PIPE MHW MEAN HIGHER HIGH WATER B.W = BOTTOM OF CURB MISC = MISCELLANEOUS BIT. = BTUNINOUS MILLW MEAN LOWER LOW WATER BW = BOTTOM OF CURB MISC = MISCELLANEOUS BIT. = BTUNINOUS MILLW MEAN LOWER LOW WATER C0 = CHANNEL MWP MEAN SPACALS C1P = GAST IRON PIPE N MILLS PER HOUR C1P = COSTRUCTION JOINT NC NOT NO CONTRACT C1P = CLEAR NTS NOT TO SCALE C0NC = CONSTRUCTION JOINT NC = NUTRER C0NC = CONTRUCTION JOINT NC = NUTRER C0NT = CONTRUCTION JOINT NC = NUTRER C0NT = CONTRUCTION SOCIETY ND NUTBER C	STANDARDS INSTITUTE	mm = MILLIMETERS
TESTING AND MATERIALSMH= MANHOLEAWS= AMERICAN WELDING SOCIETYMHHWMEAN HIGHER HIGH WATERBAD,P.= BOTTOM OF PIPEMHWMEAN HIGHER HIGH WATERBB= BACK TO BACKMIN= MINIMUMBC= BOTTOM OF CURBMISC= MISCELLANEOUSBIT.= BITUNINOUSMILW= MEAN LOW WATERC= CHANNELMPa= MEGAPASCALSCC= CORTER TO CENTERMPH= MILES PER HOURCF= CUBIC FEETMSL= MEGAPASCALSCP= CONSTRUCTION JOINTNIC= NOTT N CONTRACTCLR= CLEARNTNOT N CONTRACTCQN= CONSTRUCTION JOINTNIC= NUMERCONST= CONSTRUCTIONPVC= OLIVIN/CHLORIDECONST= CONSTRUCTIONPVC= OLIVIN/CHLORIDECONST= ODEPTHRC,P.= REINFORCINGD= DEPTHRC,P.= REINFORCINGD= DEPTHRC,P.= REINFORCINGD= DEVTHRC,P.= REINFORCINGD= DEVTHRC,P.= REINFORCINGDC= DROP CURBSANSANTARYDETU'S= DETAILSSCH= SCHEDULEDC= DROP CURBSTANCESSS = DETAILSSCH= SCHEDULEDC= DETAILSSCH= SUMICARDDI= DEPARTMENT OF DEFENSESPC= SPECFICATIONLE= EACHSQ= SUMICARDDI= DEPARTMENT OF DEFENSESPC<	APPROX= APPROXIMATE	MAX = MAXIMUM
AWS= AMERICAN WELDING SOCIETYMHHW= MEAN HIGHER HIGH WATERBLO.P.= BOTTOM OF PIPEMHW= MEAN HIGH WATERBLW= BOTTOM OF CURBMISC= MISCELLANEOUSBTT= BITUMNOUSMLW= MEAN LOW WATERBW= BOTTOM OF WALLMLW= MEAN LOW WATERCC= CORTER TO CENTERMPA= MILES PER HOURCF= CUBIC FEETMPA= MILES PER HOURCF= CUBIC FEETMSL= MEAN SEA LEVELCI= CONSTRUCTION JOINTNIC= NOTT N CONTRACTCIR= CLEARNTS= NOT N CONTRACTCONT= CONSTRUCTION JOINTNIC= NOT N CONTRACTCONT= CONSTRUCTIONNIC= NOT N CONTRACTCONT= CONSTRUCTIONNIC= NOTHCONT= CONTRUCTIONRF= REINFORCEO CONCRETE PIPECONT= CONTRUCTIONRF= REINFORCEO CONCRETE PIPEDR= DEPTHR.C.P.= REINFORCEO CONCRETE PIPEDR= DEOR DUN RIVERRCD= SOUTHDEG= DEOR CURBS= SOUTHDEG= DEOR CURBSCHSCHILLSDR= DISALSSCHSCHILLSDR= DISALSSCHSCHILLSDR= DI	ASTM = AMERICAN SOCIETY OF	MEA = MEASURED
B.O.P.= BOTTOM OF PIPEMHW= MEAN HIGH WATERBB= BACK TO BACKMIN= MINNUMBB= BATTOM OF CURBMISCMISCELLANEOUSBHT= BITUMINOUSMLW= MEAN LOW WATERBW= BOTTOM OF WALLMP= MEGAPASCALSCC= CENTER TO CENTERMPH= MIEGS PASCALSCC= CAST IRON PIPEMP= MIEGS PASCALSCJ= CONSTRUCTION JOINTNIC= NOT TO SCALECDR= CAST IRON PIPEN= NOT TO SCALECON= CONSTRUCTION JOINTNIC= NOT TO SCALECON= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONC= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONC= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONT= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONT= CONTINUOUSR/F= REINFORCINGDC= DEPTHRC.P.= REINFORCINGDC= DEPTHRC.P.= REINFORCINGDC= DERTHSCH= SCHONDC= DERTALSSCH= SCHONDC= DERARTINENSCH= SCHONDC= DERARTINENSCH= SCHONDFM> DESEL FUEL MARINESCH= SUPORTDFM= DESEL FUEL MARINESCH= SUPORTDFM= DESTARTINEN OF DEFENSESPEC= SECTIONDD= DEPARTIMENT OF DEFENSESPEC= SUPORTEE= EACHSQ= SULAREET </td <td>TESTING AND MATERIALS</td> <td>MH = MANHOLE</td>	TESTING AND MATERIALS	MH = MANHOLE
BIB= BACK TO BACKMIN= MININUMBC= BOTTOM OF CURBMISCMISCELLANEOUSBT= BITUMINOUSMILW= MEAN LOWER LOW WATERBW= CHANNELMPa= MEGAPASCALSC(C)= CENTER TO CENTERMPa= MEGAPASCALSC(T)= CAST IRON PIPEMSL= MEAN SEA LEVELC)= CONSTRUCTION JOINTNC= NOT TO SCALEC)= CONSTRUCTION JOINTNC= NOT TO SCALEC)= CONSTRUCTION JOINTNC= NOT TO SCALECONC= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONT= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONT= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONT= CONTINUOUSR/F= REINFORCED CONCRETE PIPED/R= DORN RIVERRC/D= REQUIREDD/R= DORN RIVERRC/D= SANITARYDEG= DEGREESSAN= SANITARYDETL'S= DETAILSSCH= SCICIONDIA= DISANCESHT= SHEETDIA= DISTANCESINC= SUPACIFICATIONDIA= DEFARLESQ= SOUTHDIA= DEFARLESQ= SUPACIFICATIONEA= EACHSQ= SUPACIFICATIONDIA= DEGREESSPEC= SECIFICATIONEA= EACHSQ= SUPAREEDT= DEFARLSSUP= SUPAREEA= EACHSQ= SUPAREEACH= ELEVATION (NAVD'88)	AWS = AMERICAN WELDING SOCIETY	MHHW = MEAN HIGHER HIGH WATER
BC= BOTTOM OF CURBMISC= MISCELLANEOUSBIT.= BITUMINOUSMLLW= MEAN LOWER LOW WATERBUT= BEDTTOM OF WALLMLW= MEGAPASCALSC= CHANNELMPa= MEGAPASCALSC/C= CENTER TO CENTERMPH= MILES PER HOURC/F= CUBC FEETMSL= MEAN SEA LEVELC/I= CONSTRUCTION JOINTNIC= NORTHC/I= CONSTRUCTION JOINTNIC= NOT TO SCALEC/R= CLEARNTS= NOT TO SCALEC/O= CLEAN OUTNO.= NUMBERCONST= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONST= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONST= CONSTRUCTIONRF= REDINFORCIDE CONCRETE PIPED/R= DEPTHR.C.P.= REINFORCED CONCRETE PIPED/R= DEPTHR.C.P.= REINFORCED CONCRETE PIPED/R= DEGREESSAN= SAUTHD/R= DEGREESSAN= SAUTHD/R= DEGREESSAN= SAUTHD/R= DEGREESSAN= SAUTHD/R= DISTANCESIM= SIMILARD/R= DEPARTMENT OF DEFENSESPCC= SECIFICATIOND/R= DEPARTMENT OF DEFENSESPCC= SECIFICATIOND/R= EACHSQ= SUPPORTEA= EACHSQ= SUPARTEXIT= EXITERNE HIGH WATERSTUC.= STAUCTUREEXIT= EXITENCESFC= SECIFICATION<		MHW = MEAN HIGH WATER
BIT.= BITUMINOUSMILW= MEAN LOWER LOW WATERBW= BOTTOM OF WALLMLW= MEAN LOWER LOW WATERCW= CANTER TO CENTERMLW= MEAN SACALSC/C= CENTER TO CENTERMPH= MILES PER HOURC/F= CUBIC FEETMSL= MEAN SACALSC/F= CAST IRON PIPENG= NOT IN CONTRACTCJ= CONSTRUCTION JOINTNIC= NOT NO SCALECO= CLEARNTS= NOT NO SCALECONT= CONSTRUCTION JOINTNIC= NUMBERCONT= CONSTRUCTIONPCV= POLYVIVIX CHLORIDECONT= CONSTRUCTIONPCV= POLYVIVIX CHLORIDECONT= CONTINUOUSR/F= REINFORCINGD= DEPTHR.C.P.= REINFORCINGD= DEPTHR.C.P.= REINFORCINGD= DEPTHR.C.P.= REINFORCINGD= DEPTHR.C.P.= REINFORCINGD= DEPTHRCP.= SOUTHDEG= DEPTALSSCH= SOUTHDEG= DEPTALSSCH= SOUTHDEG= DEPTALSSCH= SOUTHDEG= DESELFUEL MARINESECT= SECTIONDIST= DISTANCESIN= SINILARDDIT= DISTANCESIN= SINILARDDIT= DISTANCESIN= SINILARDDIT= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEACH= SUTENCSUPPORT= SUPORTEACH= EACH FACESS <td>B/B = BACK TO BACK</td> <td>MIN = MINIMUM</td>	B/B = BACK TO BACK	MIN = MINIMUM
BW= BOTTOM OF WALLMLW= MEAN LOW WATERC= CHANNELMPa= MEGAPASCALSC/C= CCENTER TO CENTERMPh= MLES PER HOURC/F= CUBIC FEETMSL= MEAN SEA LEVELC/P= CAST IRON PIPEN= NORTHC/R= CLEARNTS= NOT TO SCALEC/R= CLEAN OUTNO.= NUMBERC/ON= CLEAN OUTNO.= NUMBERC/ONT= CONSTRUCTION JOINTN/C= NOT TO SCALEC/N= CONSTRUCTIONPVC= POLYVINYL CHLORIDEC/ONT= CONSTRUCTIONPVC= POLYVINYL CHLORIDEC/ONT= CONSTRUCTIONPVC= REINFORCIDC/NT= CONTINUOUSR/F= REINFORCIDD/R= DEPTHR.C.P.= REINFORCIDD/R= DEGREESSAN= SAUTHD/R= DEGREESSAN= SAUTHD/R= DEGREESSAN= SAUTHD/R= DISTANCESIM= SIMILARD/R= DISTANCESIM= SIMILARD/R= DISTANCESIM= SIMILARD/R= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONL/R= EACHSQ= SOUAREEF= EACH FACESY= SAUAREEF= ELEVATION (NAVD'88)SUPP= SUPPORTELEC= LEUCTRICALSY= SOUAREEF= EACH HACESY= SOUAREEF= EACH HACESY= SOUAREEF= EACH HA	BC = BOTTOM OF CURB	MISC = MISCELLANEOUS
C= CHANNELMPa= MEGAPASCALSC/C= CENTER TO CENTERMPH= MILES PER HOURC/F= CUBIC FEETMSL= MEAN SEA LEVELC/P= CAST IRON PIPEN= NORTHCJ= CONSTRUCTION JOINTNIC= NOT IN CONTRACTCLR= CLEARNTS= NOT TO SCALECONC= CONCRETEO.C.= ON CENTERCONC= CONCRETEO.C.= ON CENTERCONST= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONT= CONTINUOUSR/F= REINFORCINGD= DEPTHR.C.P.= REINFORCIDD/R= DOWN RIVERRECO= REINFORCED CONCRETE PIPED/R= DOWN RIVERRECO= SOUTHDEG= DEGRESSAN= SANITARYDETL'S= DETAILSSCH= SCHEDULEDFM= DIESEL FUEL MARINESECT= SECTIONDAM= DIMATERSHT= SHEETDIST= DISTANCESIM= SIMILARDD0= DEPARTMENT OF DEFENSESPEC = SPECIFICATIONA= ACHSQ= SQUAREEF= EACHSQ= SQUAREET= EXTREME HIGH WATERSTILL= STRUCTUREELEC TEICALSY= SQUARE YARDETC= EXTERIORT.G.C.= TOP ON CONCRETEEXN= EACH WAYT.B.D= TOP ON CONCRETEEXN= EACH MAYT.B.D= TOP OF CONCRETEEXN= EACH MAYT.B.D= TOP OF CONCRETE		MLLW = MEAN LOWER LOW WATER
C/C= CENTER TO CENTERMPH= MILES PER HOURCF= CUBIC FEETMSL= MEAN SEA LEVELCJP= CAST IRCN PIPEN= NORTHCJ= CONSTRUCTION JOINTNIC= NOT IN CONTRACTCLR= CLEARNIS= NOT TO SCALECO= CLEANNIS= NOT TO SCALECONC= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONST= CONTINUCOUSR/F= REINFORCED CONCRETE PIPED/R= DEPTHR.C.P.= REQUIREDD/R= DEORESSAN= SANTARYDEG= DEORESSAN= SANTARYDETL'S= DETALSSCH= SCETIOND/M= DESEL FUEL MARINESECT= SECTIOND/M= DIARTERSHT= SHEETD/M= DISTANCESIM= SIMLARDOD= DEPARTMENT OF DEFENSESPEC= SPECFICATIONEA= EACHSQ= SQUAREEH= ELEVATION (NAV088)SUPP= SUPPORTELC= ELECTRICALSY= SQUARE YARDEXT= EXTERIORT.O.C= TOP OF CONCRETEEXT= EXTERIOR <td></td> <td>MLW = MEAN LOW WATER</td>		MLW = MEAN LOW WATER
CF= CUBIC FEETMSL= MEAN SEA LEVELCIP= CAST IRON PIPEN= NOR THCIP= CAST IRON PIPEN= NOR THCIR= CLEARNTS= NOT TO SCALECON= CLEAR OUTNO.= NUMBERCONC = CONSTRUCTIONPVC= POLYVINYL CHLORIDECONST= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONST= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONST= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONT= CONTINUOUSR/F= REINFORCINGD= DEPTHR.C.P.= REINFORCINGDC= DROP CURBS= SOUTHDEG= DROP CURBS= SOUTHDEG= DEGREESSAN= SANITARYDETL'S= DETALSSCH= SCHEDULEDFM= DISSEL FUEL MARINESECT= SECTIONDIA= DISTANCESIM= SIMILARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SUMARE YARDEA= EACH FACESS= STAINLESS STEELEHW= EXTREME HIGH WATERSTRUC= STRUCTUREELC= ELECTRICALSY= SUPPORTELC= ELECTRICALSY= SUPARAYEXIST.= EXTERIORT.O.S= TOP OF NORARYEXIST.= EXTERIORT.O.S= TOP OF CONCRETEEXIST.= EXTERIORT.O.S= TOP OF CONCRETEEXIST.= EXTRIGNT.O.S <td></td> <td>MPa = MEGAPASCALS</td>		MPa = MEGAPASCALS
CIP = CAST IRON PIPE N = NORTH CJ = CONSTRUCTION JOINT NIC = NOT IN CONTRACT CLR = CLEAR NTS = NOT TO SCALE CO = CLEAN OUT NO. = NUMBER CONC = CONSTRUCTION PVC = POLYVINYL CHLORIDE CONT = CONSTRUCTION PVC = POLYUNYL CHLORIDE DOT = DEPTH R.C.P. = REINFORCED CONCRETE PIPE DIR = DOWN RIVER REQUIRED = REQUIRED DET = DEGREES SAN = SAURAC DIT = DISTANCE SIMI = SIMILAR DIST = DISTANCE SIMILAR SOCTION EA = ACH SQ = SUPCIFICATION DIST = DISTANCE SIMULAR SIMULAR DIST DISTANCE		
CJ= CONSTRUCTION JOINTNICNICT IN CONTRACTCLR= CLEARNIC= NOT IN CONTRACTCLR= CLEARNIC= NOT TO SOLLECO= CLEAN OUTNO.= NUMBERCONCE= CONCRETEO.C.= ON CENTERCONST= CONSTRUCTIONPVC= POLYVINYL CHLORIDECONT= CONTINUOUSR/F= REINFORCED CONCRETE PIPEDR= DEPTHR.C.P.= REINFORCED CONCRETE PIPEDR= DEPTHR.C.P.= REINFORCED CONCRETE PIPEDR= DEGREESSAN= SANTARYDETU'S= DETALSSCH= SCTIONDIA= DIAMETERSHT= SHEETDIST= DISTANCESIM= SIMLARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SQUAREEF= EACH FACESS= STAINLESS STEELEHW= EXTREME HIGH WATERSTRUC.= STRUCTUREELEC= ELECTRICALSY= SQUARE YARDETC= TCETERAT.B.D= TO ED DETERMINEDEXIST.= EXISTINGT.B.D= TO ED EDETEMINEDEXIST.= EXISTINGT.O.C= TOP OF CONCRETEEXIST.= EXISTINGT.O.C= TOP OF CONCRETEEXIST.= EXISTINGT.O.C= TOP OF OCONCRETEF.F.= FINGHED FLOORT.O.C= TOP OF OUNCALFDN= EXISTINGT.O.C= TOP OF OUNCALFIN= FINGHEDTOP OF SITEL		MSL = MEAN SEA LEVEL
CLRCLEARINTSINT TO SCHALECOC CLEAN OUTNO.NUMBERCONCC CONCRETEO.C.ON CENTERCONTC CONSTRUCTIONPVCP OLYVINYL CHLORIDECONTC CONTRUOUSR/FE REINFORCED CONCRETE PIPED/RD OWN RIVERREQDR EQUIREDDC= DROP CURBS= SOUTHDEG= DEGREESSAN= SANTARYDETUS= DETAILSSCH= SCHEDULEDFM= DIESEL FUEL MARINESECT= SECTIONDIA= DIAMETERSHT= SHEETDIST= DISTANCESIM= SMILARDOD= DEPARTMENT OF DEFENSESPEC= SCUIREEA= EACHSQ= SQUAREEF= EACH FACESS= STAINLESS STEELEHW= EXTREME HIGH WATERSTRUC;= STRUCTUREELC= LECTRICALSY= SQUARE YARDETC= ECRTICALSY= SQUARE YARDETC= ECRTICALSY= SQUARE YARDEXT= EXISTINGTEMP= TEMPORARYEXT= EXISTINGTEMP= TEMPORARYEXT= EXISTINGTLOC= TOP OF CONCRETEEXT= EXISTINGTLOC= TOP OF CONCRETEEXPN= EXISTINGTLOC= TOP OF CURBFF.= FINISHED FLOORTC= TOP OF CURBFF.= FINISHED FLOORTC= TOP OF CURBFF.= FINISHED FLOORTC= TOP OF CURBFF.<		
CO= CLEAN OUTNO.= NUMBERCONC= CONCRETEO.C.= ON CENTERCONST= CONSTRUCTIONPVC= POLYUNYL CHLORIDECONTINUOUSRF= REINFORCINGD= DEPTHR.C.P.= REINFORCINGDC= DROP CURBS= SOUTHDEG= DEGREESSAN= SANITARYDETL'S= DETAILSSCH= SCHEDULEDAM= DIAMETERSHT= SHEETDIA= DIAMETERSHT= SHEETDIST= DISTANCESIM= SIMILARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SUARAREEHW= EXTREME HIGH WATERSTRUC= STRUCTUREEL= ELEVATION (NAVD'88)SUPP= SUPORTELC= ELECTRICALSY= SQUARE YARDETC= ETCETERAT&B= TOP AND BOTTOMEW= EACH MAYT.B.D= TO BE DETERMINEDEXIST.= EXISTINGTEMP= TEMPORARYEXIST.= EXISTINGT.O.C= TOP OF CONCRETEEXIST.= EXPANSIONT.O.S= TOP OF CONCRETEF.F.= FINISHED FLOORT.C.= TOP OF CURBF.F.= FINISHED FLOORT.C.S= TOP OF CURBF.F.= FINISHED FLOORT.O.S= TOP OF CURBF.F.= FINISHED FLOORT.C.= TOP OF CURBF.F.= FINISHED FLOORT.C.= TOP OF CURBF.F.= FINISHED FLOORT.O.S <td></td> <td>NIC = NOT IN CONTRACT</td>		NIC = NOT IN CONTRACT
CONCCONCRETEC.C.FOR CENTRECONSTCONSTRUCTIONPVCPOLYNYL CHLORIDECONSTCONTINUOUSR/F= REINFORCED CONCRETE PIPEDDEPTHR.C.P.= REINFORCED CONCRETE PIPED/RDOWN RIVERREQD= SOUTHDEGDEGREESSAN= SANITARYDETL'SDETAILSSCH= SCHEDULEDFMDIESEL FUEL MARINESECT= SECTIONDIADIAMETERSHT= SHEETDISTDISTANCESIM SIMILARDODDEPARTMENT OF DEFENSESPEC= SPECIFICATIONEAEACHSQ= SQUAREEFEACH FACESS= STAINLESS STEELEHWEXTREME HIGH WATERSTRUC_STRUCTUREELCELECATRICALSY= SQUAREETCETCETERAT.B.D= TO BE DETERMINEDEXIST.EXISTINGT.B.D= TO BE DETERMINEDEXIST.EXISTINGT.O.C= TOP OF CONCRETEEXPNEXPANSIONT.O.C= TOP OF CONCRETEF.F.FINISHED FLOORTC= TOP OF CURBF.F.FLEETU/RU/RU/R WEIGHTFWFRESH WATERW/W/TFWFRESH WATERW/W/TFWFRESH WATERW/W/TFWFRESH WATERW/W/TFWFRESH WATERW/W/TGRTNGGRADEW/W/THGALVANZEDWW/TWEIGHT <trr><td< td=""><td></td><td>NTS = NOT TO SCALE</td></td<></trr>		NTS = NOT TO SCALE
CONSTCONSTRUCTIONPVC= POLYVINVL CHLORIDECONT= CONTINUOUS R/F = REINFORCED CONCRETE PIPED/R= DOWN RIVERRC.P.= REINFORCED CONCRETE PIPED/R= DOWN RIVERREQU= REQUIREDDC= DROP CURBS= SOUTHDEG.= DEGREESSAN= SANTARYDETL'S= DEGREESSAN= SANTARYDETL'S= DEGREESSAN= SHEETDIST= DISTANCESIM= SIMILARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SUAILSEH= ELEVATION (NAVD'38)SUPP= SUPPORTELEC= ELEVATION (NAVD'38)SUPP= SUPPORTELEC= ELECATRICALSY= SQUARE YARDEXIST.= EXISTINGT.B.D= TO BE DETERMINEDEXIST.= EXISTINGT.B.D= TO BE DETERMINEDEXIST.= EXISTINGT.O.C= TOP OF CONCRETEEXIST.= EXISTINGT.O.C= TOP OF CURBFDN.= FOUNDATIONT.O.S= TOP OF STEELF.F.= FINSHED FLOORT.C= TOP OF CURBFDN.= FOUNDATIONT.O.S= UP RVERFW= FRESH WATERW= UTRANIGH MUECULAR WEIGHTFL= FLOOD LIGHTTYP= TYPICALFR= FIBERGLASS REINFORCED PLASTICUNG= UNLESS NOTED OTHERWISEFS= FRA SIDEWITHWILTRA HIGH MOLECULAR WEIGHTFW= FRESH WATER </td <td></td> <td>NO. = NUMBER</td>		NO. = NUMBER
CONT= CONTINUOUSR/F= REINFORCINGD= DEPTHR.C.P.= REINFORCINGDC= DEPTHR.C.P.= REQUIREDDC= DROP CURBS= SOUTHDEG= DEGREESSAN= SANITARYDETALSSCH= SCHEDULEDFM= DIESEL FUEL MARINESECT= SECTIONDIA= DIAMETERSHT= SHETDIST= DISTANCESIM= SIMILARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SOUTHEL= ELEVATION (NAVD'88)SUPP= SURJORTELC= ELEVATION (NAVD'88)SUPP= SURDORTELC= ECTERAT&B= TOP AND BOTTOMEW= EACH WAYT.B.D= TO BE DETERMINEDEXIST.= EXISTINGTEMPTEMPORARYEXT= EXTERIORT.O.CTOP OF CONCRETEEXTN= EXTERIORT.O.CTOP OF STEELFF.= FINISHED FLOORTC= TOP OF CURBFF.= FIBERGLASS REINFORCED PLASTICU/RU/LTA HIGH MOLECULAR WEIGHTFW= FRESH WATERW/= WITHGALVA= GRADEW/= WITHGALV= GALVANIZEDW/= WITHGALVA= GRADEW/= WITHGALVA= GRADEW/= WITHGALVA= GRADEW/= WITHGALVA= GRADEW/= WITHGALVA= GRADEW/= WITH		O.C. = ON CENTER
D= DEPTHR.C.P.= REINFORCED CONCRETE PIPED/R= DOWN RIVERREQU= REQUIREDD/R= DOWN RIVERREQU= REQUIREDDC= DROP CURBS= SOUTHDEG= DEGREESSANSANITARYDETL'S= DETAILSSCH= SCHEDULEDFM= DIESELFUEL MARINESECT= SECTIONDIA= DIAMETERSHT= SHEETDISTDISTANCESIM= SIMLARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SQUAREEF= EACH FACESS= STAINLESS STEELEHW= EXTREME HIGH WATERSTRUC.= STRUCTUREEL= ELEVATION (NAVD'88)SUPP= SUPPORTELCC= ELECATICALSY= SQUARE YARDETC= ECETRICALSY= SQUARE YARDEXTER= EXTERIORT.O.C= TOP OF CONCRETEEXTST.= EXISTINGT.O.C= TOP OF CONCRETEEXTRENCT.O.C= TOP OF ORARYEXT= EXPANSIONT.O.S= TOP OF WALLF.F.= FINISHED FLOORT.C= TOP OF CURBFDN.= FOUDDATIONTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFR= FRESH WATERW/= WIDTH MOLECULAR WEIGHTFW= FRESH WATERW/= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WALL THICKNESSGRTMG= GRADEW/= WID		PVC = POLYVINYL CHLORIDE
D/R= DOWN RIVERREQDREQUINEDDC= DROP CURBS= SOUTHDEG= DEGREESSAN= SANTARYDETL'S= DETAILSSCH= SCHEDULEDFM= DIESEL FUEL MARINESECT= SECTIONDIA= DIALISSCH= SCHEDULEDIST= DISTANCESIM= SIMILARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SQUAREEF= EACH FACESS= STAINLESS STEELEHW= EXTERME HIGH WATERSTRUC.= STRUCTUREELC= ELECTRICALSY= SQUARE YARDEICC= ELECTRICALSY= SQUARE YARDETC= ETCETERATAB= TOP AND BOTTOMEW= EACH WAYT.B.D= TO BE DETERMINEDEXIST.= EXISTINGTLMP= TEMPORARYEXT= EXTERIORT.O.C= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF WALLF.F.= FINISHED FLOORTC= TOP OF WALLF.F.= FINISHED FLOORUNOUNLESS NOTED OTHERWISEF.F.= FINISHED FLOORUN= UNLERF.F.= FINISHED FLOORWWITHGALV= GALVANZEDW </td <td></td> <td>R/F = REINFORCING</td>		R/F = REINFORCING
DCDROP CURBSSOUTHDEG> DEGREESSANSANITARYDETL'S> DETAILSSCHSCHEDULEDFM> DIESEL FUEL MARINESECTSECTIONDIADIAMETERSHTSHETDIST> DISTANCESIMSIMILARDOD> DEPARTMENT OF DEFENSESPECSPECIFICATIONEA= EACHSSSTAINLESS STEELEHW= EXTREME HIGH WATERSTRUC.STRUCTUREELC= ELEVATION (NAVD88)SUPPSUPPORTELEC= ELEVATION (NAVD88)SUPPSUPPORTELEC= EXTERME HIGH WATERTBD AND BOTTOMEW= EXCH FACESSSTAINLESS STEELEWW= EXTREME HIGH WATERSTRUC.STRUCTUREELEC= ELEVATION (NAVD88)SUPPSUPPORTELEC= ELEVATION (NAVD88)SUPPSUPARDEXT= EXISTINGT.O.CTOP ADD BOTTOMEW= EACH WAYT.B.DTO BE DETERMINEDEXT= EXISTINGT.O.CTOP OF CONCRETEEXPN= EXISTINGT.O.CTOP OF CURBFDN.= FOUNDATIONTWTOP OF GURBFDN.= FOUNDATIONTWTOP OF GURBFL= FLOOD LIGHTTYTYFV= FRESH WATERWITUNCES NOTED OTHERWISEFS= FAR SIDEUHWULTRA HIGH MOLECULAR WEIGHTFT= FEETU/RU/RUP RIVERFW= FRESH WATERWITWITH<		R.C.P. = REINFORCED CONCRETE PIPE
DEGDEGREESSANSANITARYDETL'SDETAILSSCHSCHEDULEDFMDIESELFUELMARINESECTSECTIONDIADIAMETERSHTSIMETDISTDISTANCESIMSIMILARDODDEPARTMENT OF DEFENSESPECSPECIFICATIONEAEACH FACESSSTAINLESS STEELEHWEXTREME HIGH WATERSTRUC.STRUCTUREELELEVATION (NAVD'88)SUPPSUPPORTELCCELECTRICALSYSQUARE YARDETCETCETERAT&BTOP AND BOTTOMEWEACH WAYT.B.DTO BE DETERMINEDEXIST.EXISTINGTEMPTEMPORARYEXTEXTERIORT.O.CTOP OF CONCRETEEXPANSIONT.O.STOP OF CONCRETEEXPNEXPANSIONT.O.STOP OF OF CURBFDN.FOUNDATIONTWTOP OF CONCRETEFX.FINISHED FLOORTCTOP OF CURBFLFLOOD LIGHTTYTYP ICCALFRFIBERGLASS REINFORCED PLASTICUNOUNILESS NOTED OTHERWISEFXFRESH WATERW.WITGALVGALVANIZEDWWITGALVGALVANIZEDWWITHGALVGALVANIZEDWWITGUSSGUSSETQCENTER LINEHHIGHEST ASTRONOMICAL TIDE%PERCENTHAHIGHEST ASTRONOMICAL TIDE%PERCENTHAHIGHEST ASTRONOMICAL TIDE%PERCE		REQ'D = REQUIRED
DETL'SDETAILSSCHSCHSCHEDULEDFM= DIESEL FUEL MARINESECT= SCHEDULEDIA= DIAMETERSHT= SHEETDIST= DISTANCESIM= SIMILARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SQUAREEF= EACH FACESS= STAINLESS STEELEW= EXTERME HIGH WATERSTRUC.= STRUCTUREELC= ELECATRICALSY= SQUARE YARDELC= ELECTRICALSY= SQUARE YARDELC= ELECTRICALSY= SQUARE YARDEXT= EXTERIORT.B.D= TO PAND BOTTOMEXT= EXTERIORT.O.C= TOP OF CONCRETEEXIST= EXITERIORT.O.S= TOP OF CONCRETEEXIST= EXISINGTC= TOP OF CONCRETEEXIST= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLERS NOTED OTHERWISEFS= FAR SIDEUHMW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERW/= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T= WALL THICKNESSGRING= GRADEW.T= WALL THICKNESSGRING= GRADEW.T= WALL THICKNESSGRING= GRATINGWT= UEST HAN OR EQUAL TOI= IBEAMR= PLATEHAT= HIGHEST ASTRONOMICAL TIDE%= PERECENT		
DFM= DIESEL FUEL MARINESECT= SOLUTIONDIA= DIAMETERSHT= SHEETDIST= DISTANCESIM= SIMILARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SQUAREEF= EACH FACESS= STAINLESS STEELEHW= EXTREME HIGH WATERSTRUC.= STRUCTUREEL= ELEVATION (NAVD'88)SUPP= SUPPORTELEC= ELEVANSIONT.B.D= TO BE DETERMINEDEXIST.= EXTRENCT.B.D= TO BE DETERMINEDEXIST.= EXTRENCT.O.C= TOP OF OCRETEEXPN= FOUNDATIONT.O.C= TOP OF CURBFDN.= FOUNDATIONT.W= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFR= FRESH WATERUN= UNESS NOTED OTHERWISEFS= FAR SIDEUHAW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= WIDTH OR WIDE FLANGE BEAMGR= GADEW/= WIDTH OR WIDE FLANGE BEAMGR= GUS		SAN = SANITARY
DIAE DIAMETERSHTS SHEETDIST= DISTANCESIM= SIMILARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SQUAREFF= EACH FACESS= STAINLESS STEELEHW= EXTREME HIGH WATERSTRUC.= STRUCTUREEL= ELEVATION (NAVD'88)SUPP= SUPPORTELEC= ELECARICALSY= SQUARE YARDETC= TCETERAT&B= TOP AND BOTTOMEW= EACH WAYT.B.D= TO BE DETERMINEDEXIST.= EXISTINGTEMP= TEMPORARYEXT= EXTERIORT.O.C= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF CURBFJN.= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNOUNILES NOTED OTHERWISEFS= FAR SIDEUHMW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= WITHGALV= GALVANIZEDW= WITHGALV= GALVANIZEDW= WITHGUSS = GUSSETQ= CENTER LINEH= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTHC= HANDICAPPED \leq = LESS THAN OR EQUAL TOI= 1BEAMR= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILOGRAMSX= BYKN= KILOGRA		SCH = SCHEDULE
DIST= DISTANCESIM= SIMLARDOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SQUAREEF= EACH FACESS= STAINLESS STEELEW= EXTREME HIGH WATERSTRUC.= STRUCTUREEL= ELEVATION (NAVD'88)SUPP= SUPPORTELEC= ELECTRICALSY= SQUARE YARDETC= ETCETERAT&B= TOP AND BOTTOMEW= EACH WAYT.B.D= TO BE DETERMINEDEXIST.= EXISTINGTEMP= TEMPORARYEXT= EXTERIORT.O.C= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF STEELF.F.= FINISHED FLOORTC= TOP OF CURBFDN= FOUNDATIONTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERW/= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WALL THICKNESSGRTINGGUSS= GUSSET \mathcal{Q}_{c} = CENTER LINEH= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTHC= HADDICAPPED \mathcal{L}_{c} = LESS THAN OR EQUAL TOI= IBEAMR= PLATEINV= INVERT&= AND <td></td> <td>SECT = SECTION</td>		SECT = SECTION
DOD= DEPARTMENT OF DEFENSESPEC= SPECIFICATIONEA= EACHSQ= SQUAREEF= EACH FACESS= STAINLESS STEELEHW= EXTREME HIGH WATERSTRUC.= STRUCTUREEL= ELEVATION (NAVD'88)SUPP= SUPPORTELEC= ELECTRICALSY= SQUARE YARDETC= ELECTRICALSY= SQUARE YARDETC= ETCETERAT&B= TOP AND BOTTOMEW= EACH WAYT.B.D= TO BE DETERMINEDEXIST.= EXISTINGTEMP= TEMPORARYEXT= EXTRIORT.O.C= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF FURBFDN.= FOUNDATIONTW= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLESS NOTED OTHERWISEFS= FAR SIDEUHMW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERW/= WITHGALV= GAADEW.T.= WALL THICKNESSGRTING= GRADEW.T.= WALL THICKNESSGRTING= GRADEW.T.= WEIGHTGUSS= GUSSETQ= CENTER LINEH= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTHC= HANDICAPPED 4 = LESS THAN OR EQUAL TOI <td< td=""><td></td><td>SHT = SHEET</td></td<>		SHT = SHEET
EAE ACHSQS OUAREEF= EACH FACESQ= SOUAREEF= EACH FACESS= STAINLESS STEELEHW= EXTREME HIGH WATERSTRUC. = STRUCTUREEL= ELEVATION (NAVD'88)SUPP= SUPPORTELEC= ELEVATION (NAVD'88)SUPP= SUPPORTELEC= ELEVATION (NAVD'88)SUPP= SUPPORTELE= ELEVATION (NAVD'88)TAB= TOP AND BOTTOMELE= ELEVATION (NAVD'88)TAB= TOP OAD DOTOMEXT= ELCETERAT&B= TOP OP DOT DOTHERWIDEEXTREMERINGT.O.C= TOP OF CONCRETEEXPN= EVANSIONT.O.S= TOP OF STEELF.F.= FINISHED FLOORTC= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF CURBFV= FRESH WATERU/R= UNLESS NOTED OTHERWISEFS= FAR SIDEU/R= UNHERFW= FRESH WATERW/L= WITHGALV= GALVANIZEDW= WITHGU	DIST = DISTANCE	SIM = SIMILAR
EFEACH FACESGSTAINLESS STELEHWEXTREME HIGH WATERSTRUC.STRUCTUREELELEVATION (NAVD'88)SUPPSUPPORTELECELECTRICALSYSQUARE YARDETCETCETERAT&BTOP AND BOTTOMEWEACH WAYT.B.DTO BE DETERMINEDEXIST.EXISTINGTEMPTEMPORARYEXTEXTERIORT.O.CTOP OF CONCRETEEXPNEXPANSIONT.O.STOP OF CONCRETEF.F.FINISHED FLOORTCTOP OF OF STEELF.F.FINISHED FLOORTCTOP OF OF WALLFLFLOOD LIGHTTYPTYPICALFRPFIBERGLASS REINFORCED PLASTICUNOUNLESS NOTED OTHERWISEFSFAR SIDEUHMWULTRA HIGH MOLECULAR WEIGHTFTFEETU/RUP RIVERFWFRESH WATERW/WITHGALVGALVANIZEDWWITHGALVGALVANIZEDWTWEIGHTGUSSGUSSETQCENTER LINEHHEIGHT#NUMBERHATHIGHEST ASTRONOMICAL TIDE%PERCENTHCHANDICAPPED \leq LESS THAN OR EQUAL TOII BEAMRLPLATEINVINVERT&ANDJTJOINTQATKgKILOGRAMSXBYKNKILOREMTONSØDIAMETERLLENGTH OR ANGLE/PER	DOD = DEPARTMENT OF DEFENSE	SPEC = SPECIFICATION
EHWEXTREME HIGH WATERSUPEVALUATION (NAVD'88)EL= ELEVATION (NAVD'88)SUPP= SUPPORTELEC= ELECTRICALSY= SQUARE YARDETC= ETCETERAT&B= TOP AND BOTTOMEW= EACH WAYT.B.D= TO BE DETERMINEDEXIST.= EXISTINGTEMP= TEMPORARYEXIST.= EXTERIORT.O.C= TOP OF CONCRETEEXPN= SPANSIONT.O.S= TOP OF GURBFJN.= FOUNDATIONTW= TOP OF COUREFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLESS NOTED OTHERWISEFW= FRESH WATERU/R= UP RIVERFW= FRESH WATERW/= WIDTH NOR WIDE FLANGE BEAMGR= GRADEW.T.= WAIL THICKNESSGRTING= GRADEW.T.= WIDTH NOR WIDE FLANGE BEAMGR= GRADEW.T.= WIDTH OR WIDE FLANGE BEAMH= HEIGHT $\#$ = NUMBERHAT= HIGHEST ASTRONOMICAL TIDE $\%$ = PERCENTHC= HANDICAPPED \leq = LESS THAN OR EQUAL TOI= IBEAMR= PLATEINV= INVERT& = ANDJT= JOINT $@$ = ATKN= KILOGRAMSx= BYKN= KILOREMNS\$\$= DERL= LENGTH OR ANGLE/= PER		SQ = SQUARE
EL=ELEVATION (NAVD'88)SUPP=SUPPORTELEC=ELECTRICALSY=SQUARE YARDETC=ETCETERAT&B=TO P AND BOTTOMEW=EACH WAYT.B.D=TO BE DETERMINEDEXIST.=EXISTINGTEMP=TEMPORARYEXT=EXTERIORT.O.C=TOP OF CONCRETEEXPN=EXPANSIONT.O.S=TOP OF CURBFDN.=FOUNDATIONTW=TOP OF WALLFL=FLOOD LIGHTTYP=TYPICALFRP=FIBERGLASS REINFORCED PLASTICUNO=UNLESS NOTED OTHERWISEFS=FAR SIDEUHWW=ULTRA HIGH MOLECULAR WEIGHTFT=FEETU/R=WITHGALV=GRADEW.T=WIDH OR WIDE FLANGE BEAMGR=GRADEW.T=WIDH OR WIDE FLANGE BEAMGR=GUSSETQ=CENTER LINEH=HEIGHT#NUMBERHAT=HIGHEST ASTRONOMICAL TIDE%=HC=HANDICAPPED \leq LESS THAN OR EQUAL TOI=IBEAMPL=IVV=INVERT&ANDJUN=NUVERT&ANDJUN=KILOGRAMSX=KN=KILONEWTONSØDIAMETERL <td></td> <td>SS = STAINLESS STEEL</td>		SS = STAINLESS STEEL
ELECELECTRICALSUPPSUPPSUPPSUPRETC= ELECTRICALSY= SQUARE YARDETC= ETCETERAT&B= TOP AND BOTTOMEW= EACH WAYT.B.D= TO BE DETERMINEDEXIST.= EXISTINGTEMP= TEMPORARYEXT= EXTERIORT.O.C= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF CURBF.F.= FINISHED FLOORTC= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERW/= WIDTH OR WIDE FLANGE BEAMGR= GRADEWT= WIDTH OR WIDE FLANGE BEAMGR= GRADEWT= WEIGHTGUSS= GUSSET		STRUC. = STRUCTURE
ETCETCETERAT& BETOP AND BOTTOMEWEACH WAYT&B= TOP AND BOTTOMEXIST.= EXISTINGT.B.D= TO BE DETERMINEDEXIT= EXTERIORT.O.C= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF CONCRETEF.F.= FINISHED FLOORTC= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLESS NOTED OTHERWISEFS= FAR SIDEUHWW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UVRIVERFW= FRESH WATERW/= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WALL THICKNESSGRTNG= GRADEW.T.= WEIGHTGUSS= GUSSETQ= CENTER LINEH= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTHC= HANDICAPPED \leq = LESS THAN OR EQUAL TOI= IBEAM R_{L} = PLATEINV= INVERT&ATKN= KILOGRAMSX= BYKN= KILORAMSX= BYKN= KILORAMSX= BFR		SUPP = SUPPORT
EWEACH WAYT.B.DTOP AND BOTTOMEXIST.= EXISTINGT.B.D= TOP AND BOTTOMEXT= EXTERIORT.B.D= TEMPORARYEXT= EXTERIORT.O.C= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF CURBF.F.= FINISHED FLOORTC= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLESS NOTED OTHERWISEFS= FAR SIDEUHMW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERW/= WITHGALV= GAADEW.T.= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WALL THICKNESSGRTING= GRADEW.T.= WEIGHTGUSS =GUSSETQ= CENTER LINEH= HEIGHT#NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTHC= HANDPL= LESS THAN OR EQUAL TOI= I BEAMPL= PLATEINV= INVERT&ANDJT= JOINT@= ATTkg= KILOGRAMSX= BYKN= KILORAMS X = BYKN= KILORAMS X = DIAMETERL= LENGTH OR ANGLE/= PER	ELEC = ELECTRICAL	SY = SQUARE YARD
EXIST.= EXISTINGI.B.D= IOBE DETERMINEDEXT= EXTERIORTEMP= TEMPORARYEXT= EXTERIORT.O.C= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF STEELF.F.= FINISHED FLOORTC= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLESS NOTED OTHERWISEFS= FAR SIDEUHW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERW/= WIDTH OR WIDE FLANGE BEAMGRLV= GRADEW.T.= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WEIGHTGUSS= GUSSETQ= CENTER LINEH= HEIGHT#NUMBERHAT= HIGHST ASTRONOMICAL TIDE $\%$ = PERCENTILC= HANDICAPPED \leq = LESS THAN OR EQUAL TOI= IBEAMPL= PLATEINV= INVERT $@$ = ATkg= KILOGRAMSx= BYKN= KILORAPEO \checkmark ENAL= LENGTH OR ANGLE/= PER	ETC = ETCETERA	T&B = TOP AND BOTTOM
EXIST.= EXISTINGTEMP= TEMPORARYEXT= EXTERIORT.O.C= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF STEELF.F.= FINISHED FLOORTC= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLESS NOTED OTHERWISEFS= FAR SIDEUHMW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERW/= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WALL THICKNESSGRTNG= GRADEW.T.= WEIGHTGUSS= GUSSETQ= CENTER LINEH= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTI= I BEAMPL= LESS THAN OR EQUAL TOI= I BEAMPL= DLATEINV= INVERT& ANDANDJT= JOINT@= ATTkg= KILOGRAMSx= BYKN= KILONEWTONS ϕ = DIAMETERL= LENGTH OR ANGLE/= PER	EW = EACH WAY	T.B.D = TO BE DETERMINED
EXT= EXTERIORT.O.C= TOP OF CONCRETEEXPN= EXPANSIONT.O.S= TOP OF STEELF.F.= FINISHED FLOORTC= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLESS NOTED OTHERWISEFS= FAR SIDEUHMW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERW/= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WEIGHTGUSS= GUSSETQ= CENTER LINEH= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTI= I BEAMPL= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILORENTONS ϕ = DIAMETERL= LENGTH OR ANGLE/= PFR		
EXPN= EXPANSIONT.O.S= TOP OF STEELF.F.= FINISHED FLOORTC= TOP OF CURBFDN.= FOUNDATIONTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLESS NOTED OTHERWISEFS= FAR SIDEUHW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERW/= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WALL THICKNESSGRTNG= GRADEW.T.= WEIGHTGUSS= GUSSETQ= CENTER LINEH= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTI= I BEAMPL= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILORTHOR ANGLE \checkmark = PER	EXT = EXTERIOR	
FDN.= FOUNDATIONTC= TOP OF CORBFL= FLOOD LIGHTTW= TOP OF WALLFL= FLOOD LIGHTTYP= TYPICALFRP= FIBERGLASS REINFORCED PLASTICUNO= UNLESS NOTED OTHERWISEFS= FAR SIDEUHMW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERW/= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WALL THICKNESSGRTNG= GRATINGWT= WEIGHTGUSS= GUSSET \mathbb{Q} = CENTER LINEH= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTHC= HANDICAPPED \leq = LESS THAN OR EQUAL TOI= I BEAMRL= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILORAMSx= BYKN= KILONEWTONS ϕ = DIAMETERL= LENGTH OR ANGLE//= PER		
FL=FLOOD LIGHTTW=TOP OF WALLFRP=FIBERGLASS REINFORCED PLASTICTYP=TYPICALFR=FAR SIDEUNO=UNLESS NOTED OTHERWISEFS=FAR SIDEUHW=ULTRA HIGH MOLECULAR WEIGHTFT=FEETU/R=UP RIVERFW=FRESH WATERW/=WITHGALV=GALVANIZEDW=WIDTH OR WIDE FLANGE BEAMGR=GRADEW.T.=WALL THICKNESSGRTNG=GRATINGWT=WEIGHTGUSS=GUSSET $\[mathbb{Q}\]$ =CENTER LINEH=HEIGHT#=NUMBERHAT=HIGHEST ASTRONOMICAL TIDE $\[mathbb{N}\]$ =PERCENTHC=HANDICAPPED $\[mathbb{L}\]$ =PERCENTINV=INVERT&=ANDJT=JOINT@=ATkg=KILORAMSx=BYKN=KILONEWTONS $\[mathbb{Q}\]$ =DIAMETERL=LENGTH OR ANGLE/=PER		TC = TOP OF CURB
FRP =FIBERGLASS REINFORCED PLASTICUNO=ITTPLAL FS =FAR SIDEUNO=UNLESS NOTED OTHERWISE FT =FEETU/R=ULTRA HIGH MOLECULAR WEIGHT FW =FRESH WATERU/R=UP RIVER $GALV$ =GALVANIZEDW=WITH $GALV$ =GRADEW.T.=WIDTH OR WIDE FLANGE BEAM GR =GRADEW.T.=WALL THICKNESS $GRTNG$ =GRATINGWT=WEIGHT $GUSS$ =GUSSET Q =CENTER LINEH=HEIGHT#NUMBERHAT=HIGHEST ASTRONOMICAL TIDE%=PERCENTHC=HANDICAPPED \leq =LESS THAN OR EQUAL TOI=I BEAMR=PLATEINV=INVERT&=ANDJT=JOINT@=ATkg=KILORAMSX=BYKN=KILONEWTONSØ=DIAMETERL=LENGTH OR ANGLE/=PER	FDN. = FOUNDATION	TW = TOP OF WALL
FS= FAR SIDEUHW= ULTRA HIGH MOLECULAR WEIGHTFT= FEETU/R= UP RIVERFW= FRESH WATERU/R= UP RIVERGALV= GALVANIZEDW= WIDTH OR WIDE FLANGE BEAMGR= GRADEW.T.= WILT HICKNESSGRTNG= GRATINGW.T.= WALL THICKNESSGUSS= GUSSETQ= CENTER LINEH= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTHC= HANDICAPPED \leq = LESS THAN OR EQUAL TOI= I BEAMR= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILONEWTONSØ= DIAMETERL= LENGTH OR ANGLE/= PER		TYP = TYPICAL
FT=FEETU/R=OLITRA HIGH MOLECULAR WEIGHTFW=FRESH WATERU/R=UP RIVERFW=FRESH WATERW/=WITHGALV=GALVANIZEDW=WIDTH OR WIDE FLANGE BEAMGR=GRADEW.T.=WALL THICKNESSGRTNG=GRATINGWT=WEIGHTGUSS=GUSSET WT =WEIGHTH=HEIGHT#=NUMBERHAT=HIGHEST ASTRONOMICAL TIDE%=PERCENTHC=HANDICAPPED \leq =LESS THAN OR EQUAL TOI=IBEAMRL=PLATEINV=INVERT&=ANDJT=JOINT@=ATkg=KILOGRAMSx=BYKN=KILONEWTONS ϕ =DIAMETERL=LENGTH OR ANGLE//=PER	FRP = FIBERGLASS REINFORCED PLASTIC	UNO = UNLESS NOTED OTHERWISE
FW=FRESH WATER $W/$ = $WIVER$ GALV=GALVANIZEDW= $WIDTH OR WIDE FLANGE BEAM$ GR=GRADEW.T.= $WALL THICKNESS$ GRTNG=GRATINGWT= $WEIGHT$ GUSS=GUSSET $Q_{\rm L}$ =CENTER LINEH=HEIGHT#=NUMBERHAT=HIGHEST ASTRONOMICAL TIDE%=PERCENTHC=HANDICAPPED \leq =LESS THAN OR EQUAL TOI=IIBEAMPL=INV=INVERT&=ANDJT=JOINT@=ATkg=KILOGRAMSX=BYKN=KILONEWTONSØ=DIAMETERL=LENGTH OR ANGLE/=PER	FS = FAR SIDE	UHMW = ULTRA HIGH MOLECULAR WEIGHT
$GALV$ = GALVANIZEDW= WIDTH OR WIDE FLANGE BEAM GR = GRADEW.T.= WIDTH OR WIDE FLANGE BEAM GR = GRADEW.T.= WALL THICKNESS $GRTNG$ = GRATINGWT= WEIGHT $GUSS$ = GUSSET Q_{L} = CENTER LINE H = HEIGHT#= NUMBER HAT = HIGHEST ASTRONOMICAL TIDE%= PERCENT HC = HANDICAPPED \leq = LESS THAN OR EQUAL TO I = I BEAMPL= PLATE INV = INVERT&= AND JT = JOINT@= AT kg = KILOGRAMS x = BY KN = KILONEWTONS ϕ = DIAMETER L = LENGTH OR ANGLE/= PER	FT = FEET	U/R = UP RIVER
GR = GRADEW= WIDTH OR WIDE PLANGE BEAM $GRTNG$ = GRATINGW.T.= WALL THICKNESS $GRTNG$ = GRATINGWT= WEIGHT $GUSS$ = GUSSET Q_{L} = CENTER LINE H = HEIGHT#= NUMBER HAT = HIGHEST ASTRONOMICAL TIDE%= PERCENT HC = HANDICAPPED \leq = LESS THAN OR EQUAL TO I = I BEAM P_{L} = PLATE INV = INVERT&= AND JT = JOINT@= AT kg = KILOGRAMSx= BY KN = KILONEWTONS ϕ = DIAMETER L = LENGTH OR ANGLE/= PER	FW = FRESH WATER	W/ = WITH
GRTNG = GRATINGW.T.= WALL THICKNESSGUSS = GUSSET WT = WEIGHTH= HEIGHT Q = CENTER LINEHAT= HIGHEST ASTRONOMICAL TIDE $%$ = PERCENTHC= HANDICAPPED \leq = LESS THAN OR EQUAL TOI= I BEAMPL= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILONEWTONS ϕ = DIAMETERL= LENGTH OR ANGLE/= PER	GALV = GALVANIZED	W = WIDTH 0R WIDE FLANGE BEAM
GUSS= GUSSET \mathbb{Q}_{-} = CENTER LINEH= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTHC= HANDICAPPED \leq = LESS THAN OR EQUAL TOI= I BEAMPL= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILONEWTONSØ= DIAMETERL= LENGTH OR ANGLE/= PER		W.T. = WALL THICKNESS
H= HEIGHT $\#$ = NUMBERHAT= HIGHEST ASTRONOMICAL TIDE $\#$ = NUMBERHC= HANDICAPPED \checkmark = PERCENTHC= I BEAMPL= LESS THAN OR EQUAL TOI= I BEAMPL= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILONEWTONSØ= DIAMETERL= LENGTH OR ANGLE/= PER		WT = WEIGHT
H= HEIGHT#= NUMBERHAT= HIGHEST ASTRONOMICAL TIDE%= PERCENTHC= HANDICAPPED \leq = LESS THAN OR EQUAL TOI= I BEAMPL= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILONEWTONS ϕ = DIAMETERL= LENGTH OR ANGLE/= PER		وَ = CENTER LINE
HC= HANDICAPPED \checkmark = PERCENTI= I BEAM \checkmark = LESS THAN OR EQUAL TOI= I BEAMPL= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILONEWTONSØ= DIAMETERL= LENGTH OR ANGLE/= PER		
HC= HANDICAPPED \leq = LESS THAN OR EQUAL TOI= I BEAMPL= PLATEINV= INVERT&= ANDJT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILONEWTONS ϕ = DIAMETERL= LENGTH OR ANGLE/= PER		% = PERCENT
INV= INVERT&= PLATEJT= JOINT&= ANDJT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILONEWTONSØ= DIAMETERL= LENGTH OR ANGLE/= PER		
INV = INVERT&= AND JT = JOINT@= AT kg = KILOGRAMSx= BY KN = KILONEWTONS ϕ = DIAMETERL= LENGTH OR ANGLE/= PER	I = I BEAM	
JT= JOINT@= ATkg= KILOGRAMSx= BYKN= KILONEWTONS ϕ = DIAMETERL= LENGTH OR ANGLE/= PER	INV = INVERT	
kg= KILOGRAMSx= BYKN= KILONEWTONS ϕ = DIAMETERL= LENGTH OR ANGLE/= PER		@ = AT
KN= KILONEWTONS ϕ = DIAMETERL= LENGTH OR ANGLE/= PER	6	0
L = LENGTH OR ANGLE / = PER		ϕ = DIAMETER
LAT = LOWEST ASTRONOMICAL TIDE		-
	LAT = LOWEST ASTRONOMICAL TIDE	




ISSUED FOR BID










X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Civil\DWG\Sheets\SHT-C100-EX.dwg





X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Civil\DWG\Sheets\SHT-C100-EX.dwg





X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Civil\DWG\Sheets\SHT-C100-EX.dwg


DESCRIPTION















X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Civil\DWG\Sheets\SHT-C200-STORM.dwg








X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Civil\DWG\Sheets\SHT-C200-STORM.dwg




















X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Civil\DWG\Sheets\SHT-C300-GRADING.dwg













X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Civil\DWG\Sheets\SHT-C400-MATERIALS.dwg














X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Civil\DWG\Sheets\SHT-C500-DTL.dwg









REV BY DATE DESCRIPTION


ISSUED FOR BID URBAN ENGINEERS, INC. 530 Walnut Street Philadelphia, PA 19106 (215) 922-8080 Fax (215) 922-8082 DCATION CAMDEN, NJ SJPC BALZANO MARINE TERMINAL RAIL INFRASTRUCTURE REHABILITATION PROPOSED SITE DETAILS 1 NO. GE50867 DWN GJB PROJ # 2021500064.000 CHK MJT DATE 06/24/2022 DRAWING NUMBER C-501



5 HYDRANT DETAIL


X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Civil\DWG\Sheets\SHT-C500-DTL.dwg






REV BY DATE DESCRIPTION


EĮ	45'(1/8)				45'(1/8) { 22+1/2'(1/16)			6)	11-1/4'(1/32)			
٤	·A :	В	C	Ð	A	В	C	5	A 3	В	C	Ð
61	2.5	15	:2	.02	7.5	الثا ر	9"	.02	7.5	" 81	7"	.07
	2.5" :	24	\$ 4 ⁶	.04	2.5"	24	11	.04	2.5	24	91	.03
•	(2.5°)	20"	\$9°	.07	2.5" :	39.	16	.07	2.5	28	25*	.Q6



1) PIPE BOLLARD PLAN VIEW

ISSUED FOR BID





	ISSUED FOR BID
NUMBER OF NEW	URBAN ENGINEERS, INC. 530 Walnut Street Philadelphia, PA 19106 (215) 922-8080 Fax (215) 922-8082
	CAMDEN, NJ
	SJPC BALZANO MARINE TERMINAL RAIL INFRASTRUCTURE REHABILITATION PROPOSED SITE DETAILS 3
	DWN GJB PROJ # 2021500064.000 DRAWING NUMBER CHK MJT DATE 06/24/2022 C-503

DESCRIPTION

REV BY DATE

GENERAL NOTES.

GE	NERAL NOTES:			8.7. Painting - see specifications.8.8. Beams bearing on masonry shall have angle wall an
1.	Building Code, Design Reference Codes & Standards1.1.International Building Code (IBC) 20181.2.AISC Manual of Steel Construction - 15th Edition - ASD1.3.AWS Structural Welding Code D1.41.4.Building Code Requirements for Reinforced Concrete - A1.5.Building Code Requirements for Masonry Structures - TM1.6.Minimum Design leads for Building and Other Structures	<i>I</i> IS 402-16		 8.9. Miscellaneous hanging loads shall be applied so tha 8.10. Steel supplier to provide all deck support angles (as ends of each joist, etc. 8.11. The steel supplier shall include an additional 5% of t 8.12. Weld masonry anchors (provided by mason) to stru vertically.
2.	 1.6. Minimum Design Loads for Buildings and Other Structure <u>Design Loads</u> 2.1. Design Live Loads 2.1.1. Floor Live Loads 2.1.2. Roof Live Load (min) 2.2. Design Roof Snow Load (ASCE 7-16) 2.2.1.1. Crownd Crownload 	150 psf 20 psf	9.	 <u>Steel Deck</u> 9.1. Deck detailing, fabrication and erection in accordance 9.2. Shop drawings are required and shall note type of el supervision of a registered professional engineer. 9.3. All metal decks shall be securely fastened (welded, in 9.4. Provide deck continuous over at least 3 supports an and provide shoring as required by the Steel Deck Interview.
	 2.2.1. Ground Snow Load 2.2.2. Flat-Roof Snow Load 2.2.3. Snow exposure factor 2.2.4. Importance factor 2.2.5. Thermal factor 2.3. Design Wind Loads (ASCE 7-16) 2.3.1. General 2.3.1.1. Basic Wind Speed 2.3.1.2. Risk Category 2.3.1.3. Exposure Category 	Pg=25 psf $Pf=21 psf$ $Ce=1.0$ $I=1.0$ $Ct=1.2 (Canopy)$ $V=112 mph (Ultimate)$ II C	10.	 <u>Special Inspection - Structural</u> 10.1. The owner will retain an approved independent testin testing shall be sent to Architect and Engineer within 10.2. Continuous Inspection Contractor shall notify inspection to be inspected shall be removed and replaced at the 10.3. Periodic Inspection Contractor shall notify inspect to be inspected shall be removed and replaced at the 10.4. Materials Testing Contractor shall employ a testing 10.5. Special Inspection Testing shall include: 10.5.1. Concrete: mix data, daily pour reports, cyling
	 2.4. Design Seismic Loads (ASCE 7-10) 2.4.1. Importance Factor 2.4.2. Risk Category 2.4.3. Mapped Spectral Response Acceleration 2.4.4. Mapped Spectral Response Acceleration 2.4.5. Site Class (assumed soil characteristics) 2.4.6. Spectral Response Coefficient 2.4.7. Spectral Response Coefficient 2.4.8. Seismic Design Category 	le=1.0 II Ss=0.179g S1=0.047g D SDs=0.191g SD1=0.075g B		 1705.3. 10.5.2. Structural Steel: Per IBC 2018 Section 1705 10.5.3. Cold Formed Steel Deck: Per IBC 2018 Section 10.5.4. Masonry: Per IBC 2018 Section 1705.4 and 10.5.5. Soils: Per IBC 2018 Section 1705.6 and Tab 10.5.6. Foundations: Per IBC 2018 Sections 1705.7 10.5.7. Special Inspections for Wind Resistance: Pe 10.5.8. Special Inspections for Seismic Resistance:
3.	Material Properties3.1.Concrete minimum compressive strength (28 days) 3.1.1.3.1.1.Maximum water/cement ratio 3.1.2.3.1.2.Slump3.2.Reinforcing bars (ASTM A615 Gr 60)3.3.Welded wire reinforcement (ASTM A1064)3.4.Non-composite deck (ASTM A653)3.5.Composite deck (ASTM A653)3.6.Structural steel W/S Shapes (ASTM A992)3.7.Structural steel other shapes (ASTM A36)3.8.Structural steel tubes (ASTM A500 Gr C)3.9.Structural steel pipe (ASTM A53 Gr B or A501)3.10.Masonry (ASTM C90)3.11.Masonry grout (ASTM C1019)	f'c=4 ksi w/c=0.40 max. 3" +/- 1" fy=60 ksi fy=60 ksi fy=33 ksi fy=33 ksi fy=50 ksi fy=50 ksi fy=50 ksi fy=35 ksi f'm=1,500 psi 1,900 psi (2,150 psi) 2,000 psi		
4.	Soil Properties			

4. Soil Pronerties

5011 Pr	operties	
4.1.	Net Allowable Bearing Pressure - Shallow (virgin soil)	1500 p
4.2.	Net Allowable Bearing Pressure - Shallow (engineered fill)	1500 p
4.3.	Unit weight of fill	120 pc
4.4.	Active pressure Coefficient	Ka=0.3
4.5.	Pressure at Rest Coefficient	Ko=0.
4.6.	Friction	f=0.3

5. General

5.1. The Contractor shall verify all dimensions in the field prior to commencing any work. The Engineer shall be notified of any discrepancies.

- 5.2. Any discrepancies between the architectural and structural drawings shall be brought to the attention of the Architect and Structural Engineer for resolution prior to commencing work.
- 5.3. Shop drawings must be checked and stamped by the Contractor prior to submission. Drawings not first reviewed and approved by the Contractor will be returned with no action taken.
- 6. Foundations
- 6.1. Existing foundations
- 6.1.1. Existing foundations shown on drawings are approximate exact size and location must be verified during construction.
- 6.1.2. Unless otherwise noted, the bottom of new footings shall match the bottom of existing footing elevation.
- 6.2. Locate existing underground utilities in areas of construction before you dig. Coordinate with utility companies for shut off requirements of active lines. 6.3. Contractor shall protect all excavations, including structures which may be involved, with proper safeguards including bracing and shoring as necessary.

7. Concrete

- 7.1. All concrete construction shall be in accordance with ACI 318 Building Code Requirement for Reinforced Concrete, the ACI Detailing Manual and
- Project Specifications Section 033000 Cast-In-Place Concrete. See Section 1 for governing editions.
- 7.2. Provide sloped concrete floor surfaces in accordance with ADA code requirements.
- 7.3. Provide shop drawings which indicate size, spacing, and bend details of all reinforcing.
- 7.4. Furnish bar and wire mesh supports and chairs where necessary to hold reinforcing in place.
- 7.5. Welding of reinforcing bars or mesh is not permitted without approval from Structural Engineer.
- 7.6. Reinforcing for slabs on grade shall be as shown on plans. All reinforcing shall be supported on chairs to maintain position during concrete placement, unless noted otherwise.
- 7.7. Length of reinforcing splices shall conform to ACI Building code requirements. All reinforcing steel lap splices not detailed on drawings shall be Class B tension splices unless noted otherwise. Where embedment length is not shown use ACI tension development length. All bends or hooks shown shall be ACI standard, unless noted otherwise.
- 7.8. Contractor has the option to use mechnical splices in place of lap splices. Mechanical splices type and location shall be submitted to engineer for approval.

8. <u>Structural Steel</u>

- 8.1. All structural steel shall be fabricated and installed in accordance with Project Specifications Section 05 12 00 Structural Steel Framing. All steel detailing, fabrication and erection in accordance with AISC Specifications and Code of Standard Practice and the AWS Structural Welding Code. See Section 1 for governing edition. 8.2. Fabricator shall be AISC quality certified.
- 8.3. Shop drawings are required and shall note type of electrodes, size of all welds, and type/size of all bolts. Shop drawings shall be prepared under the supervision of a registered professional engineer.
- 8.4. Calculations for all moment connections and any non-standard shear connections (ie., skewed, extended or any other connection when designated by the engineer of record) shall be submitted with their corresponding fabrication drawing. Calculations to be sealed by a professional engineer registered in the New Jersey.
- 8.5. Connections high strength bolted:
- 8.5.1. A325-SC with hardened washers for all moment connections, hangers and other connections as noted on the drawings. All slip critical bolting (shop & field) to be inspected by a qualified testing laboratory approved by the Architect/Structural Engineer.
- 8.5.2. A325-N with hardened washers for all other connections.
- 8.5.3. Use standard holes unless noted otherwise. 8.5.4. Where reaction is noted, develop same. Where not noted, provide minimum number of bolts per schedule.
- 8.6. Connections welded:
- 8.6.1. Welding electrodes shall be E70xx unless other is required for compatibility with base metal.
- 8.6.2. A currently certified welder shall perform all welding.
- 8.6.3. Do not weld to existing steel without approval from Structural Engineer.
- 8.6.4. All welding (shop & field) to be inspected by a qualified testing laboratory approved by the Architect/Structural Engineer.

anchors and bear a minimum of 6" into the wall. Masonry shall be built tightly around the beam. that no torsional loading is induced.

(as required for steel deck) for such cases as changes in joist direction, roof elevation changes, at the

of the total contract (deck & red iron) in the bid for miscellaneous use in site conditions. structural members where masonry abuts or faces structural members on 16" c/c both horizontally and

ance with SDI Manual of Construction with Steel Deck. See Section 1 for governing edition. of electrodes, size of all welds and type/size of all fasteners. Shop drawings shall be prepared under the

ed, screwed or powder-actuated pinned) to steel supports per SDI specifications. and weld to supports as indicated on plans. Limit deflection to L/240 when loaded with wet concrete k Institute.

esting laboratory that shall provide inspections and testing per ASTM E329. Reports of inspection and thin 48 hours of testing.

nspection agency and architect prior to work requiring continuous inspection -- any work completed replaced at the contractors expense.

bection agency and architect when work is ready for inspection. Any work that subsequently hides work t the contractors expense.

sting and inspection agency to perform materials testing as required by the Special Inspector.

/linder tests, slump, entrained air tests, temperature, etc. per IBC 2018 Section 1705.3 and Table


705.2 and AISC 360-16 Section N5. ection 1705.2.2. and the quality assurance program requirements of TMS 402. Table 1705.6. 5.7-1705.9 and Tables 1705.7 & 1705.8.


Per IBC 2018, Section 1705.11. nce: Per IBC 2018, Section 1705.12.

REV	ΒY	DATE	DESCRIPTION

STRUCTURAL ABBREVATIONS & SYMBOLS

ATOR	ABOVE TOP OF RAIL	00	ON CENTER
BLDG.	BUILDING	OF	OUTSIDE FACE
BM.	BEAM	PEB	PRE-ENGINEERED BUILDING
BOT.	BOTTOM	PG	PLATE GIRDER
B/S	BOTTOM OF STEEL	PJF	PREFORMED JOINT FILLER
BRCG.	BRACING	PROV.	PROVIDE
CCJ	CRACK CONTROL JOINT	REINF.	REINFORCEMENT/REINFORCING
CJ	CONSTRUCTION JOINT	SC	SLIP CRITICAL CONNECTION
CTJ	CONTRACTION JOINT	SLV	SHORT LEG VERTICAL
COL.	COLUMN	STIFF.	STIFFENER
CONC.	CONCRETE	STL	STEEL
CONN.	CONNECTION	T&S	TEMPERATURE AND SHRINKAGE
CONT.	CONTINUOUS	THK	THICK
CONTR.	CONTRACTOR	T/S	TOP OF STEEL
CWR	CONTINUOUS WELDED RAIL	T/C	TOP OF CONCRETE
DET.	DETAIL	T/	TOP OF
DIA.	DIAMETER	T,	TOP
DWL.	DOWEL	ТҮР	TYPICAL
DNL.	DOWN	UNO	UNLESS NOTED OTHERWISE
DWG.	DRAWING	WWR	WELDED WIRE REINFORCING
EA	EACH	W/	WITH
EF	EACH FACE	W/O	WITHOUT
EW	EACH WAY	W/O	SLOPE DOWN
EL.	ELEVATION		SEOFE DOWN
EL. EJ	EXPANSION JOINT		SPAN OR REINFORCING STEEL DIRECTION
FF		Ę.	CENTER LINE
	FINISHED FLOOR FOUNDATION	-	
FDN.		@	AT
FRP	FIBERGLASS REINFORCED PLASTIC	<u></u> ዊ	PLATE
FS	FAR SIDE	(A)	COLUMN LINE
GALV.	GALVANIZED		ODENINO
GB	GRADE BEAM		OPENING
HGR.	HANGER	23	
HORZ.	HORIZONTAL	_ (SECTION OR DETAIL NUMBER
HP	HIGH POINT	A	
К	KIPS		
LB.	POUND	S206	
LDCC	LOW DENSITY CONCRETE MATERIAL		DRAWING ON WHICH DETAIL IS LOCATED
LLV	LONG LEG VERTICAL		
LP	LOW POINT		
MAX.	MAXIMUM		
M.B.M.	METAL BUILDING MANUFACTURER	- b -	TOP OF CONCRETE SPOT ELEVATION
MIN.	MINIMUM	I	
N.A.	NEUTRAL AXIS		
NS	NEAR SIDE		
N.T.S.	NOT TO SCALE		






	1		
REV	BY	DATE	DESCRIPTION

NOTES


1. SEE STRUCTURAL GENERAL NOTES SHEET S-000.

LEGEND

	NEW 18'-0" ROLL-UP DOOR
	EX DOOR (ACCESSIBLE OR NON-ACCESSIBLE)
$\Box \Box \Box$	60' BOX CAR
. Д	NEW LOADING DOCK
	DEMOLITION



		ISSUED FOR BID
andagagagagagagagagagagagagagagagagagaga		ENGINEERS, INC. 530 Walnut Street ladelphia, PA 19106 8080 Fax (215) 922-8082
E OF NEW CAR	CAMDEN,	NJ
Coordination	SJPC BALZANO MAR RAIL INFRASTRUCTURE LOADING DOCK PLA	REHABILITATION N AT SHED 1 -
ONAL ENTITIE	PLAN AND SE	CTION
-~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	^{DWN} FYC ^{PROJ #} 2021500064.000 ^{CHK} MGW ^{DATE} 06/24/2022	drawing number S-101





REV BY	DATE	DESCRIPTION

- 2. ALL WORK ON THIS SHEET ASSOCIATED WITH ADD ALTERNATE #1.




	W REIN	IF. CONC	SLAB SECTION
	1'	2'	Scale: 3/4" = 1'-0"
GRAPH	IC SCALE		






X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Structural\S-103 CANOPY FRAMING PLAN AT BUILDING A AND SECTIONS.dwg

┝─┼┤		
REV BY	DATE	DESCRIPTION






REV	BY	DATE	DESCRIPTION


 DWN
 FYC
 PROJ # 2021500064.000
 DRAWING

 CHK
 MGW
 DATE
 06/24/2022
 DRAWING

S-104



X.\2021500064.000 - sipc balzano rail rehab\technical\civil\dwg\xref\UEI-TITLEBLOCK-24X22.dv



GENERAL NOTES:

1) THE INFORMATION SHOWN PERTAINING TO THE PRESENCE OF EXISTING FACILTIES AND INFRASTRUCTURE OF THE SITE AND PROPOSED WORK DEPICTED HEREON, WERE DEVELOPED IN CONJUNCTION WITH INFORMATION PROVIDED BY THE SOUTH JERSEY PORT CORPORATION (SJPC). THIS INFORMATION CONSISTED OF HISTORICAL PLANS, DRAWINGS AND RECORD DOCUMENTS REVIEWED BY URBAN ENGINEERS. THE INFORMATION SHOWN IS BASED ON A CORRELATION OF THESE RECORD PLANS AND OTHER INFORMATION COLLECTED DURING FIELD INSPECTIONS CONDUCTED BY URBAN ENGINEERS DURING THE FALL OF 2020 AND THE SPRING AND SUMMER OF 2021. THE COLLECTED INFORMATION IS BELIEVED TO BE ACCURATE AS OF THE DATE OF PREPARATION OF THESE PLANS, HOWEVER URBAN ENGINEERS ASSUMES NO LIABILITIES FOR INACCURACIES, INCONSISTANCIES, ERRORS OR OMISSIONS RELATING TO INFORMATION CONTAINED IN SUCH RECORD DOCUMENTS.

2) THE BALZANO TERMINAL, FORMERLY KNOWN AS THE BECKETT STREET TERMINAL, IS AN OPERATING PORT FACILITY THAT HAS BEEN IN SERVICE FOR APPROXIMATELY 100 YEARS. CHANGES HAVE OCCURRED OVER TIME THAT MAY NOT HAVE BEEN DOCUMENTED. LOCATIONS OF ON AND OFF-SITE UTILITIES SHOWN ARE APPROXIMATE AND MAY NOT BE COMPLETE. THE NATURE AND EXACT LOCATION OF EXISTING UTILITIES SHOULD BE VERIFIED PRIOR TO INITIATING ANY ACTIVITY THAT MAY AFFECT OR IMPACT THEIR USE OR LOCATION.

3) URBAN ENGINEERS ASSUMES NO LIABILITIES NOR TAKES ANY RESPONSIBILITY FOR IMPACTS TO THE WORK DEPICTED ON THESE DRAWINGS RESULTING FROM SUBSEQUENT CHANGES TO THE EXISTING FACILITIES NOR ANY PROPOSED PLANS OR WORK FOR CONSTRUCTION, MODIFICATION, RETIREMENT OR REMOVAL OF THE EXISTING FACILTIES EITHER OWNED OR CONTROLLED BY SJPC, ITS HEIRS, ASSIGNS, DESIGNEES, LESSORS, TENNANTS, OR OTHER GOVERNMENTAL AUTHORITIES HAVING INTERESTS IN AND ABOUT THE BALZANO TERMINAL SITE.

4) IN ACCORDANCE WITH N.J.S.A. 48:2-73 et seq. and enabling rules - N.J.A.C. 14:2, THE CONTRACTOR SHALL COMPLETE AN 811 ONE-CALL NOTIFICATION BY DIALING 811 FROM WITHIN NEW JERSEY OR BY CALLING (800)272-1000, A MINIMUM OF THREE (3) BUSINESS DAYS PRIOR TO PERFORMING ANY EXCAVATIONS. THE CONTRACTOR SHALL VERIFY LOCATIONS AND DEPTH OF ALL UNDERGROUND UTILITIES AND STRUCTURES AND COORDNATE ACTIVITIES WITH THE WORK OF OTHER TRADES AND CONTRACTORS THAT MAY BE PERFORMING CONSTRUCTION ACTIVITIES CONCURRENTLY, PRIOR TO START OF THE WORK FOR THIS PROJECT.

5) THE TOPOGRAPHICAL INFORMATION ILLUSTRATED HEREIN WAS DEVELOPED FROM GROUND SURVEY PERFORMED BY COLLIERS ENGINEERING AND DESIGN DURING THE SUMMER OF 2021 UTILIZING 3D LASER SCANNING EQUIPMENT AND REFERENCED TO THE NEW JERSEY STATE PLANE COORDINATE SYSTEM AND NAVD88 VERTICAL DATUM. UNDERGROUND UTILITIES SHOWN ARE BASED ON BEST AVAILABLE INFORMATION COMPILED FROM AVAILABLE DOCUMENTATION PROVIDED BY SJPC, HOWEVER, NEITHER THE SJPC NOR URBAN ENGINEEERS REPRESENTS THAT THE DRAWINGS ARE COMPLETELY ACCURATE. THE LOCATIONS SHOWN MAY BE APPROXIMATE, AND OLDER OR PREVIOUSLY ABANDONED UTILITIES MAY NOT BE SHOWN.

6) THE DRAWINGS SHOW THE PROPOSED SCOPE OF TRACK CONSTRUCTION OR REHABILITATION AND OTHER INFRASTRUCTURE IMPROVEMENTS TO BE INCLUDED WITHIN THE SCOPE OF THIS PROJECT. THE CONTRACTOR SHALL NOTIFY THE SJPC AND THE PROJECT MANAGER IMMEDIATELY UPON DISCOVERY OF THE PRESENCE OF EXISTING UNDERGROUND UTILITIES THAT DO NOT COMPLY WITH THE MINIMUM REQUIREMENTS FOR DEPTH OF COVER BENEATH RAILROAD TRACKS OR ARE NOT SHOWN ON THE PLANS AND WHICH MAY BE IN CONFLICT WITH WORK TO BE PERFORMED UNDER TERMS OF THE CONTRACT WITH THE SJPC.

7) WHERE PROPOSED RAILROAD TRACK CONSTRUCTION OR REHABILITATION IS SHOWN TO PASS OVER EXISTING UNDERGROUND UTILITIES AS INDICATED ON THE PLANS AND THAT ARE NOT PRESENTLY PROTECTED FROM LOADS IMPOSED BY THE MOVEMENT OF RAILROAD LOCOMOTIVES OR ROLLLING STOCK, THE CONTRACTOR MUST INSTALL CASING PIPES TO PROTECT ANY EXISTING UTILTY LINES CARRYING SUBSTANCES UNDER PRESSURE BENEATH TRACKS. THE CONTRACTOR MUST SUBMIT SITE SPECIFIC PLANS FOR EACH SUCH LOCATION IN ACCORDANCE WITH THE PROJECT SPECIFICATIONS, TO THE SJPC AND PROJECT MANAGER FOR PRIOR REVIEW AND APPROVAL BEFORE COMMENCING SUCH OPERATIONS.

8) THE QUANTITY FOR "RESTORATION OF PAVEMENT" WILL BE ADJUSTED UP OR DOWN BASED ON FINAL FIELD MEASUREMENTS. UNBALANCING OF THIS BID ITEM ON THE PROPOSAL FORM WILL BE CAUSE FOR REJECTION OF THE BID.

9) SOME LOCATIONS WHERE WORK WILL OCCUR IN THE PROJECT HAVE GROUND SURFACES OTHER THAN PAVEMENT, SUCH AS GRAVEL OR SILTY EARTH. THE CONTRACTOR SHALL RESTORE ALL SUCH LOCATIONS TO THE PRE-CONSTRUCTION CONDITIONS AFTER PERFORMANCE OF THE WORK. PAYMENT FOR SUCH RESTORATION WORK IN THESE AREAS WILL NOT BE MADE DIRECTLY BUT SHALL BE SUBSIDIARY FOR OTHER ITEMS FOR WHICH PAYMENT IS MADE.

10) THE CONTRACTOR SHALL TAKE NECESSARY PRECAUTIONS IN EXCAVATIONS AND SHALL HAND EXCAVATE AS NEEDED TO PROTECT EXISTING UNDERGROUND STRUCTURES AND UTILITIES. THE CONTRACTOR SHALL PLATE OVER TRENCHES AS NECESSARY FOR MAINTAINING PEDESTRIAN AND VEHICULAR TRAFFIC DURING THE WORK.

SURVEY NOTES

X.\2021500064.000 - sipc balzano rail rehab\technical\civil\dwg\xref\UEI-TITLEBLOCK-24X22.dwg

1. RAILROAD STATIONING FOR PROJECT PROFILES AND ALIGNMENTS IS BASED ON STATIONS ESTABLISHED FOR CHORD DEFINITION CURVES AT THE CENTERLINE OF THE PROPOSED TRACK UNLESS OTHERWISE NOTED.

2. THE CONTRACTOR IS RESPONSIBLE FOR THE PRESERVATION OF ALL SURVEY CONTROL MONUMENTS. IN THE EVENT MONUMENTS ARE DAMAGED OR DESTROYED BY THE CONTRACTOR, THE ENGINEER WILL REPLACE THE MONUMENT AT THE CONTRACTOR'S SOLE COST AND EXPENSE.

ABBREVIATIONS

MISCEL	LANEOUS
BLVD. BLDG. C.Y. CONC. DIA. DR. DWG. ELEV. EXIST. F.S. HORIZ. 'INCH, INV. LT. L.F. MAX. MIN. NAVD NGVD NTS NO. OH PROP. RR RWY R/W RT. S.F. STA. STD. ST. TWP. TYP. UG V WT. W X-ING	AVENUE BOULEVARD BUILDING CUBIC YARDS CONCRETE DEGREE (S) DIAMETER DRIVE DRAWING EAST ELEVATION EXISTING FOOT, FEET OR MINUTE (S) FINISHED SURFACE HORIZONTAL INCHES OR SECOND (S) INVERT LEFT LENGTH LINEAL FEET MAXIMUM MINIMUM NORTH NORTH AMERICAN VERTICAL DATUM NATIONAL GEODETIC VERTICAL DATUM NATIONAL GEODETIC VERTICAL DATUM NOT TO SCALE NUMBER OVERHEAD PROPOSED RAILROAD RAILWAY RIGHT OF WAY RIGHT OF WAY RIGHT OF WAY RIGHT OF WAY RIGHT OF WAY SUARE FEET STATION STANDARD STREET TOWNSHIP TYPICAL UNDERGROUND VELOCITY WEIGHT
<u>TRACK</u> atr	ABOVE TOP OF RAIL

ATR	ABOVE TOP OF RAIL
ALIGN.	ALIGNMENT
BBR	BELOW BASE OF RAIL
CNTRS.	CENTERS
CWR	CONTINUOUS WELDED RAIL
D.F.	DIRECT FIXATION
DSPD	DOUBLE SWITCH POINT DERAIL
EOT	END OF TRACK
HH	HEAD HARDENED
JTD.	JOINTED RAIL
LH	LEFT HAND
LLT	LAST LONG TIMBER
ML	MAIN LINE
MM	MILE MARKER
MP	MILE POST
NSC OTM PCC PC PCS POC PF PI POS POT PS PSC PST PTS PVC PVI PVT RBM RH SH SMSG SSPD TC T.F. UXO	NOT SUFFICIENT CLEARANCE OTHER TRACK MATERIAL POINT OF COMPOUND CURVE POINT OF CURVE TO SPIRAL POINT OF CURVE TO SPIRAL POINT OF CURVE TO SPIRAL POINT OF INTERSECTION POINT OF INTERSECTION OF TURNOUT POINT OF INTERSECTION OF TURNOUT POINT ON SPIRAL POINT OF SWITCH POINT OF SPIRAL TO CURVE POINT OF SPIRAL TO TANGENT POINT OF TANGENT POINT OF TANGENT TO SPIRAL POINT OF VERTICAL CURVE POINT OF VERTICAL INTERSECTION POINT OF VERTICAL INTERSECTION POINT OF VERTICAL TANGENT RAIL BOUND MANGANESE RIGHT HAND SECOND HAND SOLID MANGANESE SELF GUARDED SINGLE SWITCH POINT DERAIL TRACK CENTERS TRACK FEET TRACK UNIVERSAL CROSS-OVER

—— F.W. —	— F.W.	——— F.W. ——	- EXISTING FIRE WATER LINE
Ex-W	Ex-W	₩Ex-₩	EXISTING WATER LINE
· — — U[о — —	- — UD — -	- UNDER DRAIN
— — —SS-		—ss— — –	- EXISTING STORM SEWER
— — —ABN-₩- —	-ABN-₩	– −ABN−₩– – −ABN-	-' ABANDONED WATER LINE
SAN		— SAN —	- EXISTING SANITARY SEWER
S		- S ——	EXISTING STEAM LINE
—— IWW —		— IWW ———	- EXISTING WASTEWATER LINE
======	=====	=======================================	EXSISTING DUCT BANK
— — GAS — —	— GAS — —	GAS GAS	EXISTING GAS LINE
D		– D –––––	- DRAIN LINE
— cs —	- cs ——	– cs —— cs -	COMBINED SEWER
——————————————————————————————————————	—— ОНЕ —	OHE	OVERHEAD ELECTRIC
——— E ·		— E —	OTHER ELECTRIC LINE
— UGE — — —	UGE — — —	UGE – – – UGE –	UNDERGRADE ELECTRIC
			CHAIN LINK FENCE W/BARBEI
X	— — ×	×	CHAIN LINK FENCE
O		O	STEEL PIPE HANDRAIL
X		—×—— — –	· RESIDENTIAL CHAIN LINK FE
——— FM		—— FM ———	FORCE MAIN
SFM — S	FM S	SFM ————————————————————————————————————	SANITARY FORCE MAIN
JO	JO	JO	JOURNAL OIL LINE
— LO —	— LO -	LO	LUBE OIL LINE
— WO —	WO -	WO	WASTE OIL LINE
FUEL	FUEL	FUEL	MISC.FUEL LINE
— DF —	DF	DF	DIESEL FUEL LINE
— CA —	CA	CA —	COMPRESSED AIR LINE
— OIL ———	— OIL —	O/L	MISC.OIL LINE
LPG -		LPG	LPG LINE
— MCI —	— MCI -	——— MC I ———	MCI U.G. CABLE
— AT&T ——	— AT&T -	——————————————————————————————————————	AT&T U.G. CABLE
- PT&T	— PT&T —	—— PT&T ——	SPRINT U.G. CABLE
— WU —	WU -	WU	WESTERN UNION U.G. CABLE
		COM	COMMUNICATION LINE
— FOC ——	— <i>FOC</i> —	<i>FOC</i>	FIBER OPTIC LINE
E&T&TV		E&T&TV	ELECTRIC, TELEPHONE AND T
			LIMIT OF DISTURBANCE AND
LD -		— LD ———	LIMIT OF DISTURBANCE
		SF	SILT FENCE
? _		?	UNKNOWN UTILITY LINE
		PL — PL —	PROPERTY LINE
			SINGLE SIDE GUIDERAIL
			DOUBLE SIDE GUIDERAIL
			PIPELINE WITH CASING SLEE
			NOISE BARRIER WALL

KISTING WATER LINE NDER DRAIN ISTING STORM SEWER ANDONED WATER LINE ISTING SANITARY SEWER KISTING STEAM LINE KISTING WASTEWATER LINE KSISTING DUCT BANK KISTING GAS LINE RAIN LINE MBINED SEWER ERHEAD ELECTRIC THER ELECTRIC LINE NDERGRADE ELECTRIC HAIN LINK FENCE W/BARBED WIRE HAIN LINK FENCE TEEL PIPE HANDRAIL ESIDENTIAL CHAIN LINK FENCE DRCE MAIN ANITARY FORCE MAIN URNAL OIL LINE JBE OIL LINE ASTE OIL LINE IISC.FUEL LINE ESEL FUEL LINE IMPRESSED AIR LINE ISC.OIL LINE PG LINE U.G. CABLE T&T U.G. CABLE PRINT U.G. CABLE ESTERN UNION U.G.CABLE IMMUNICATION LINE BER OPTIC LINE LECTRIC, TELEPHONE AND TELEVISION IMIT OF DISTURBANCE AND SILT FENCE IMIT OF DISTURBANCE ILT FENCE KNOWN UTILITY LINE ROPERTY LINE INGLE SIDE GUIDERAIL DUBLE SIDE GUIDERAIL IPELINE WITH CASING SLEEVE DISE BARRIER WALL

REV	ΒY	DATE	DESCRIPTION

CO	CLEANOUT
<u>6</u> -0	EXISTING FIRE HYDRANT
\bigcirc	MANHOLE
	INLET
×XX.XX'	PROPOSED SPOT ELEVATION
< (MW)	MONITORING WELL
EB	ELECTRIC PULL BOX
\bigcirc GV \bigcirc WG	EXISTING WATER VALVE
G	GAS VALVE BOX
М	METER PIT
~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~~	CONTINUATION ON OTHER SHEET
Ô	PROPOSED FIRE HYDRANT
$\phi$	UTILITY POLE
$\bigcirc \langle$	UTILITY POLE w/PULLOFF GUY
$\bigcirc - \bigcirc$	UTILITY POLE w/COBRAHEAD LIGHT
×	AREA DOWN LIGHT
	PROPOSED HAYES "WD" BUMPER
	EXISTING RAILS
	EXISTING TRACK CENTERLINES
	PROPOSED TRACK CENTERLINES
	EXISTING TRACKS TO BE REMOVED
	EXISTING TRACK TO REMAIN IN PLACE INCLUDED IN NEW GEOMETRY
<u>۴</u> ــــــــــــــــــــــــــــــــــــ	PROPOSED TURNOUT
	LIMITS OF CONCRETE FOR PROPOSED FULLY EMBEDDED TRACK CONSTRUCTION
	CENTERLINE OF TRACK Alternate additional bid item

## **ISSUED FOR BID**

**URBAN ENGINEERS, INC.** 530 Walnut Street **ENGINEERS** (215) 922-8080 Fax (215) 922-8082 CAMDEN, N.J.

AWING NUMBER

S.J.P.C. BALZANO MARINE TERMINAL RAIL INFRASTRUCTURE REHABILITATION GENERAL NOTES AND LEGEND

JRBAr

[′]^ℕ FST ^{PI}


- A . A


No.

D: 240E04337000 C

111111

G-02





# **FIGURE A** CIRCULAR CURVES WITH SPIRAL TRANSITION

] - TOTAL INTERSECTION ANGLE

 $\theta_{\rm S}$  - SPIRAL ANGLE =  $\frac{A L^2}{2}$ 

 $\Delta$  - CENTRAL ANGLE OF CIRCULAR CURVE =  $1-2 \theta_s$ 

Dc - DEGREE OF CURVE

A - RATE OF CHANGE OF DEGREE OF CURVE PER 100-ft. OF LENGTH =  $\frac{Dc}{I}$ 

R - RADIUS OF CIRCULAR CURVE

T - TANGENT LENGTH OF CIRCULAR CURVE = R TAN  $\frac{\Delta}{2}$ 

L - LENGTH OF CIRCULAR CURVE =  $\frac{\Delta}{Dc} \times 100$ 

PS - TANGENT TO SPIRAL

PSC - SPIRAL TO CURVE


PCS - CURVE TO SPIRAL

PT - SPIRAL TO TANGENT

MAIN TAN PI - POINT OF INTERSECTION OF MAIN TANGENTS

(TS IN) (TS OUT) - TANGENT LENGTH OF COMPLETE CURVE = (R+o) TAN  $\frac{1}{2}$ + t

(WHEN SPIRALS OF EQUAL LENGTH ARE USED ON BOTH SIDES OF CIRCULAR CURVE, SEE FIGURE C. FOR o AND t ).



# FIGURE C SPIRAL TRANSITION CURVE SPIRAL TRANSITION CURVE DATA: THE SPIRAL USED IS DEFINED BY THE TALBOT SPIRAL.

LS = LENGTH OF SPIRAL (TS TO PSC)

$$\theta s = \frac{AL^2}{2}$$

- $X = 100 L_{1} 0.000762A {}^{2}L_{1}^{5}$
- Y =  $0.291AL_{1}^{3} 0.00000158A_{1}^{3}$
- o =  $0.0727 \text{AL}_{1}^{3}$
- t =  $50L_1 0.000127A_1^2L_1^5$

$$ST = \frac{1}{SIN \theta S}$$

$$LT = X - \frac{Y}{TAN \theta S}$$

 $Dc = 2 SIN^{-1}(50/R) = DEGREE OF CURVE (CHORD DEFINITION)$ 

L₁ - TOTAL NO. OF STATIONS IN SPIRAL

SPI - SPIRAL POINT OF INTERSECTION


NOTE: Dc,  $\theta_{S}$ ,  $\Delta$ , and  $I_{ARE}$  in degrees. All others dimensions are feet.

# FIGURE B SIMPLE CIRCULAR CURVE


- R = RADIUS OF CIRCULAR CURVE
- $\Delta$  = CENTRAL ANGLE OF CIRCULAR CURVE

$$T = R TAN \frac{2}{2}$$


$$L = \frac{\Delta}{Dc} \times 100$$



میں میں اور میں میں اور میں میں اور میں میں اور میں	مریدی <u>ہ</u>	land and a second	
	S L TRAN	NSIT SHED #4	
			\





REV	ΒY	DATE	DESCRIPTION





TH #4 EXT.	BERTH #4						EDGE OF DOCK
REMOVE EX TONGUE & AND RESTO	KISTING	7 7 7 1 2 1 2 1 2 1 2 1 2 1 2 1 2 2 1 2 2 1 2 2 1 2 2 2 2 1 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2 2	5	GANTRY CRANE GANTRY CRANE RAIL (TYP.)		G - WEST BERTH TRACK -	
	EXISTING D.F. TRACK EMBEDDED IN CONCRETE. SEE DETAIL 2/T-26 FOR SELECTIVE DEMOLITION LIMITS	5.				EAST BERTH TRACK	
26.78	22+00-	21+50-	21+00-	20 + 50 - 20 + 50 -			19+0
97+ 27 U&K. MH RINS 7.67'					GANTRY CRANE RAIL (TYP.)		
		/~					
			ASPHALT				

REV	ΒY	DATE	DESCRIPTION












REV	ΒY	DATE	DESCRIPTION







REV	BY	DATE	DESCRIPTION

# SHEET 5

# NO WORK THIS SHEET

ISSUED FOR BID

URBAN ENGINEERS, INC. 530 Walnut Street Philadelphia, PA 19106 (215) 922-8080 Fax (215) 922-8082

CAMDEN, N.J.

S.J.P.C. BALZANO MARINE TERMINAL RAIL INFRASTRUCTURE REHABILITATION PROPOSED TRACK CONSTRUCTION



No.

= 70: 24GE04337000 Algan Collaber

///11

AWING NUMBER ^R T-6

Horizontal Alignment Name: Pr-South Lead		Horizontal Alignment Name: Pr-Shed 1-2 Lead		Horizontal Alignment Name: Pr-West Berth Track Ex	tended	Horizontal Alignment Name	Pr-Building A Lead		
Element: TANGENT	EASTING 15850.76	STATION NORTHI Element: TANGENT		STATION Element: TANGENT		STING	STATION	NORTHING	EASTING
Tangent Direction: N 6°33′20.23′′E Tangent Length: 30.00	15850.76 15854.19	EXISTING PS 1:6LH -2+44.91 403452. APPARANT TOPI -2+26.11 403454. Tangent Direction: N 83°20′36.52″ W Tangent Length: 18.80	07 315454.64 25 315435.96	PS 1:8RH TURNOUT #2 15+40.15 TOPI TURNOUT #2 15+70.75 Tangent Direction: S 6°35′42.86″ W Tangent Length: 30.60	401870.01 314 401839.61 314	909.82 906.30 Tangent Directio Tangent Lengt	7+66.32 S 6°37′44.63′′W	403291.82 402598.13	315227.07 315146.45
Tangent Direction: N 0°35′49.59′′W Tangent Length: 46.90	15854.19 15853.70	Element: TANGENT APPARANT TOPI -2+26.11 403454. PC BEGIN NEW CONSTR1+89.00 403452. Tangent Direction: S 87°08′54.38″ W Tangent Length: 37.10	25 315435.96 41 315398.91	Element: TANGENT TOPI TURNOUT #2 PC Tangent Direction: S 13°44′52.76″ W Tangent Length: 106.63	401839.61 3149 401736.03 3148	Element: CURVE 96.30 80.96 PI CC PT	7+66. 32 8+52. 51 9+36. 56 478. 34	402598.13 402512.51 402653.35 402435.75	315146.45 315136.50 314671.31 315097.29
PI 2+17.94 402215.60 3 Radius: 262.04	15853.70 15852.95 15591.67 15815.49	Element: CURVE PC BEGIN NEW CONSTR1+89.00 403452. PI -0+96.22 403447. CC -0+17.98 403259. PT -0+17.98 403372. Radius: 193.19	41315398.9179315306.2446315408.5258315251.91	Element: CURVE PC PI CC PT Dudi ou Element: CURVE 16+77.39 17+07.28 17+36.99 17+36.99	401736.033148401706.993148401622.353153401677.293148	Radiu Delt 80.96 Degree of Curvature Chord 73.86 Lengt 45.60 Length Chorded 70.42 Tangen	20°25′46.43″ Rio 12°00′00.00″ 170.56 170.25 86.19	gh†	
Degree of Curvature Chord : 22°00'00.00" Length: 140.59 Length Chorded : 139.73 Tangent: 72.03 Chord: 138.91		Radius:       193.19         Delta:       51°18′28.45″ Left         Degree of Curvature Chord:       30°00′00.00″         Length:       173.00         Length:       171.03         Tangent:       92.78         Chord:       167.27         Middle Ordinate:       19.04		PT 17+36.99 Radius: 478.34 Delta: 7°09'09.90" Le Degree of Curvature Chord : 12°00'00.00" Length: 59.72 Length Chorded : 59.61 Tangent: 29.90 Chord: 59.68	ft	Chor Middle Ordinat Externa Tangent Directio Radial Directio Chord Directio	אני (.58 ד. 70 הייג S 6°37′44.63′′ W הייג N 83°22′15.37′′ W הייג S 16°50′37.85′′ W		
Middle Ordinate: External: Tangent Direction: Radial Direction: Chord Direction: Radial Direction: Radial Direction: N 58°39′44.90″E Tangent Direction: N 31°20′15.10″W		Middle Ordinate: External: Tangent Direction: Radial Direction: Chord Direction: N 2°51'05.62''W Chord Direction: S 61°29'40.15''W Radial Direction: N 54°09'34.08''W		Chord: 59.68 Middle Ordinate: 0.93 External: 0.93 Tangent Direction: S 13°44′52.76″ W Radial Direction: N 76°15′07.24″ W Chord Direction: S 10°10′17.81″ W Radial Direction: N 83°24′17.14″ W		Radial Directio Tangent Directio Element: TANGENT PT TOPI TURNOU Tangent Directio	9+36.56 #4 10+29.78	402435.75 402352.74	315097.29 315054.89
Element: TANGENT PT 2+17.94 402215.60 3	515815.49 15813.13	Tangent Direction: S 35°50′25.92″ W Element: TANGENT	58 315251.91	Tangent Direction: S 6°35′42.86″ W	401677.29 3148	Tangent Lengt	יה 93.21	402352.74	315054.89
Tangent Direction: N 31°20′15.10′′W Tangent Length: 4.53 Element: CURVE		PT -0+17.98 403372. PC 0+19.17 403342. Tangent Direction: S 35°50′25.92″ W Tangent Length: 37.15	46 315230.16	PT 17+36.99 TOPI TURNOUT #1 23+93.03 Tangent Direction: S 6°35′42.86″ W Tangent Length: 656.03	401677.29 3148 401025.60 3147	Tangent Directio Tangent Lengt	RNOUT #4 10+60.39 רוי S 27°03′ 31.07″ W רוי 30.61	402325.49	315040.97
PI 3+49.47 402327.95 3 CC 402061.92 3 PT 4+61.89 402356.89 3 Radius: 302.94	15813.13 15747.08 15554.38 15623.42	Element: CURVE PC PI CC PT Radius: PC 0+19.17 0+87.34 0+87.34 403342. 0+87.34 403287. 403189. 1+51.74 262.04	46315230.1620315190.2403315442.5849315182.32	Element: TANGENT TOPI TURNOUT #1 23+93.03 PS 1:8RH 24+23.63 Tangent Direction: S 6°35′42.86″ W Tangent Length: 30.60	401025.60 3147 400995.20 3147	95.08 91.56 Element: TANGENT PS 1:8LH TU TOPI TURNOU Tangent Directio Tangent Lengt	「#3 11+80.02 h: S 27°03′31.07′′ W	402325.49 402218.95	315040.97 314986.55
Delta:       45°29'25.86" Left         Degree of Curvature Chord:       19°00'00.00"         Length:       240.52         Length Chorded:       239.42         Tangent:       127.01         Chord:       234.26		Delta: 29°09′52.00′′ Left Degree of Curvature Chord : 22°00′00.00′′ Length: 133.38 Length Chorded : 132.57 Tangent: 68.17		Element: TANGENT PS 1:8RH TURNOUT #1 24+23.63 EOT 25+75.01 Tangent Direction: S 6°35′42.86″ W Tangent Length: 151.38	400995.20 3147 400844.82 3147	91.56 74.17 Element: TANGENT TOPI TURNOU PS 1:8 RH T Tangent Directio Tangent Lengt	「#3 11+80.02 JRNOUT #3 12+10.61 า: S 27°03′31.07′′ W า: 30.61	402218.95 402191.70	314986.55 314972.63
Middle Ordinate:23.56External:25.55Tangent Direction:N 31°20′15.10″ WRadial Direction:N 58°39′44.90″ EChord Direction:N 54°04′58.03″ WRadial Direction:N 13°10′19.05″ E		Middle Ordinate: 8.44 External: 8.72 Tangent Direction: S 35°50′25.92″ W Radial Direction: N 54°09′34.08″ W Chord Direction: S 21°15′29.93″ W		Horizontal Alignment Name: Pr- East Berth Track		CIINC			
Element: TANGENT PT 4+61.89 402356.89 3	15623.42	Radial Direction: N 83°19′26.07″ W Tangent Direction: S 6°40′33.93″ W Element: TANGENT	49 315182.32	STATION Element: TANGENT MEET SOUTH LEAD 13+80.00 PS 1:8RH TURNOUT #2 15+40.15		STING 28.21 09.82			
PC 6+96.35 402410.32 3 Tangent Direction: N 76°49′40.95″ W Tangent Length: 234.46 Element: CURVE	15395.13	PT 1+51.74 403219. PC 8+76.03 402500. Tangent Direction: S 6°40′33.93″ W Tangent Length: 724.29	11 315098.12	Tangent Direction: S 6°35′42.86″W Tangent Length: 160.15 Element: TANGENT					
PC6+96.35402410.323PI9+43.08402466.543CC402060.503	15395.13 15154.88 15313.26 15016.16	Element: CURVE PC PI CC PT Radius: B+76.03 9+17.69 9+17.69 402500. 9+17.69 402458. 402541. 9+58.71 402419. 359.26	88 314741.29	PS 1:8RH TURNOUT #2 15+40.15 TOPI TURNOUT #2 15+70.75 Tangent Direction: S 6°35′42.86″ W Tangent Length: 30.60 Element: TANGENT	401870.01 3149 401839.61 3149	09.82 06.30			
Degree of Curvature Chord : 16°00′00.00″ Length: 432.41 Length Chorded : 431.00 Tangent: 246.73 Chord: 406.78		Delta: 13°13′47.12″ Right Degree of Curvature Chord : 16°00′00.00″ Length: 82.96 Length Chorded : 82.69 Tangent: 41.66 Chord: 82.77		TOPI TURNOUT #2 15+70.75 PC 22+26.78 Tangent Direction: S 6°35′42.86″ W Tangent Length: 656.03 Element: CURVE	401839.61 3149 401187.92 3148	06. 30 30. 96			
Middle Ordinate: External: Tangent Direction: Radial Direction: Chord Direction: Radial Direction: S 68°41′30.06″ W Radial Direction: N 55°47′18.93″ W Tangent Direction: S 34°12′41.07″ W		Middle Ordinate: 2.39 External: 2.41 Tangent Direction: S 6°40′33.93″ W Radial Direction: N 83°19′26.07″ W Chord Direction: S 13°17′27.49″ W Radial Direction: N 70°05′38.95″ W		PC 22+26.78 PI 22+56.68 CC PT 22+86.39 Radius: 478.34 Delta: 7°09′09.75″ Ri	401158.223148401242.863143401129.183148	30.96 27.52 55.78 20.42			
Element: TANGENT PT 11+27.35 402262.50 3 TOPI TURNOUT #3 11+80.01 402218.95 3	15016.16 14986.55	Tangent Direction: S 19°54′21.05″ W Element: TANGENT PT 9+58.71 402419. TOPI TURNOUT #4 10+29.78 402352.	56 315079.09 74 315054.89	Degree of Curvature Chord : 12°00′00.00′′ Length: 59.71 Length Chorded : 59.61 Tangent: 29.90 Chord: 59.68					
Tangent Direction: S 34°12′41.07″ W Tangent Length: 52.66 Element: TANGENT TOPI TURNOUT #3 11+80.01 402218.95 3 PS 1:8RH TURNOUT #3 12+10.61 402191.70 3	14986.55 14972.63	Tangent Direction: S 19°54′21.05″ W Tangent Length: 71.06 Element: TANGENT TOPI TURNOUT #4 10+29.78 402352.	74 315054.89	Middle Ordinate: 0.93 External: 0.93 Tangent Direction: S 6°35′42.86″ W Radial Direction: N 83°24′17.14″ W Chord Direction: S 10°10′17.73″ W					
Tangent Direction: S 27°03′31.07′′W Tangent Length: 30.61 Element: TANGENT	14972.63	PS 1:8LH TURNOUT #4 10+60.39 402325. Tangent Direction: S 27°03′31.07″ W Tangent Length: 30.61 Element: TANGENT	49 315040.97	Radial Direction: N 76°15′07.39″ W Tangent Direction: S 13°44′52.61″ W Element: TANGENT PT 22+86.39	401129.18 3148	20.42			
PC 12+16.47 402186.48 3 Tangent Direction: S 27°03′31.07″W Tangent Length: 5.86	14969.96	PS 1: 8LH TURNOUT #4 10+60.39 402325. TOPI TURNOUT #3 11+80.02 402218. Tangent Direction: S 27°03′31.07″ W Tangent Length: 119.63	49       315040.97         95       314986.55	TOPI TURNOUT #1 23+93.02 Tangent Direction: S 13°44′52.61″ W Tangent Length: 106.63 Element: TANGENT	401025.60 3147	95.08			
PI 12+83.40 402126.88 3 CC 402017.81 3	14969.96 14939.52 15300.16 14931.83	Element: TANGENT TOPI TURNOUT #3 11+80.02 402218. PS 1:8 RH TURNOUT #3 12+10.61 402191. Tangent Direction: S 27°03′31.07″ W Tangent Length: 30.61	95 314986.55 70 314972.63	TOPI TURNOUT #1 23+93.02 PS 1:8RH TURNOUT #1 24+23.62 Tangent Direction: S 6°35′42.86″ W Tangent Length: 30.60	401025.60 3147 400995.20 3147	95.08 91.56			
Delta: 20°27′48.21″ Left Degree of Curvature Chord : 15°30′00.00″ Length: 132.43 Length Chorded : 132.02 Tangent: 66.93									
Chord: 131.72 Middle Ordinate: 5.90 External: 5.99 Tangent Direction: S 27°03′31.07″ W Radial Direction: N 62°56′28.93″ W									ED FOR BID
Chord Direction: S 16°49′36.96″W Radial Direction: N 83°24′17.14″W Tangent Direction: S 6°35′42.86″W Element: TANGENT						OF NEW			GINEERS, INC.
PT 13+48.49 402060.40 3	14931.83 14928.21					D: 24GE04337000	LOCATION CA	MDEN, N.J. ZANO MARINE TE RUCTURE REHAB	ERMINAL BILITATION


082 Oben Collins RAIL INFRASTRUCTURE REHABILITATION HORIZONTAL TRACK GEOMETRY DATA


DWN FST PROJ#

снк


[™] T-10

DRAWING NUMBER








RIPTION




## ISSUED FOR BID







REV BY DATE DES



URBAN ENGINEERS, INC. 530 Walnut Street Philadelphia, PA 19106 (215) 922-8080 Fax (215) 922-8082


CAMDEN, N.J.

S.J.P.C. BALZANO MARINE TERMINAL RAIL INFRASTRUCTURE REHABILITATION PROPOSED TOP OF RAIL PROFILES - 2 OF 2

WN FST PROJ#

T-14

DRAWING NUMBER




REV	ΒY	DATE	DESCRIPTION


T-20

AWING NUMBER

mmm

VN FST





1) ARRANGEMENT IS SHOWN FOR RECOMMENDED LOCATION AND SPACING OF DOUBLE TONGUE SWITCH FASTENING PLATES THRU TURNOUT. THE CONTRACTOR MAY PROPOSE ALTERNATE MEANS FOR SETTING THE ALIGNMENT AND PROFILE OF THE TURNOUT COMPONENTS. CONTRACTOR SHALL SUBMIT COMPLETE DRAWINGS AND PRODUCT SPECIFICATIONS, INCLUDING PROPOSED LOCATIONS OF REINFORCING STEEL FOR ANY SUCH PROPOSED ALTERNATE METHODS PRIOR TO PROCUREMENT. THE ENGINEER IS UNDER NO OBLIGATION TO APPROVE ALTERNATE MEANS OF SUCH INSTALLATION.

2) RAIL BOUND MANGANESE FROG SHOWN. SOLID MANGANESE FROG CONFORMING TO AREMA STANDARD PLAN 671 MAY BE SUBSTITUTED. SOLID MANGANESE SELF GUARDED FROGS ARE NOT PERMITTED.

3) REFER TO AREMA BASIC PLAN 989 FOR ALTERNATE ARRANGEMENT OF OPERATING MECHANISM LOCATED OUTSIDE OF GAUGE.

4) FOR ADDITIONAL DETAILS OF DOUBLE TONGUE SWITCH NOT SHOWN, REFER TO AREMA PLAN 987.

5) SUPPLIER TO SUBMIT COMPLETE SHOP DRAWINGS AND LAYOUT PLANS FOR TURNOUT AND ALL TURNOUT COMPONENTS INCLUDING TYPE OF POSITIVE RESTRAINT RAIL FASTENING SYSTEM TO BE EMPLOYED, TO THE ENGINEER FOR REVIEW PRIOR TO COMMENCING FABRICATION.

6) REFER TO SHEET T-23 FOR DETAILS OF TRANSITION SLABS.

7) REFER TO DETAIL 2/T-25 FOR SWITCH POINT MECHANISM DRAIN.

NO SCALE

2 T-21

REV	ΒY	DATE	DESCRIPTION






RAWING NUMBER

CAMDEN, N.J.






WN FST PROJ#

URBAN

T-21




1- THE SIGN SHALL BE 6061-T6 ALUMINUM SHEETING .081" THICK, WITH ONE SIDE COVERED WITH NO.2870 SILVER SCOTCHLITE AND NO.605 BLACK SCOTCHCAL LETTERS.

2- "CLOSE CLEARANCE" SIGNS SHALL BE DISPLAYED WHERE OBJECTS DO NOT PROVIDE FOR FULL CLEARANCE PER RAILROAD'S CLEARANCE DIAGRAM. THE SIGNS SHALL BE ATTACHED TO THE SIDE OF A BUILDING OR OTHER FLAT SURFACE AND SHALL BE HELD AWAY FROM THE SURFACE ABOUT 1 WITH FURRING STRIPS OR SPOOLS TO ALLOW FOR VENTILATION. NO.14 STAINLESS STEEL ROUND HEAD WOOD SCREWS OR  $\frac{1}{2}$ " diameter stainless steel bolts shall be used to attach the signs. STAINLESS STEEL WASHERS WASHERS SHALL BE USED UNDERTHE HEADS OF BOLTS OR SCREWS.


3- "CLOSE CLEARANCE" SIGNS SHALL BE ILLUMINATED DURING THE HOURS OF DARKNESS.

CLOSE CLEARANCE SIGNS NO SCALE






X.\2021500064.000 - sipc balzano rail rehab\technical\civil\dwg\xref\UEI-TITLEBLOCK-24X22.dw



	DV		RECORDIN
REV	Βĭ	DATE	DESCRIPTIO



1) THE SIGN SHALL BE 6061-T6 ALUMINUM SHEETING .081" THICK, WITH ONE SIDE COVERED WITH NO.2870 SILVER SCOTCHLITE AND NO. 605 BLACK SCOTCHCAL LETTERS.

2) SIGN AS SHOWN IS ONE SIDE ONLY.FOR BI-DIRECTIONAL VISIBILITY, MOUNT TWO SIGNS BACK TO BACK.

MATERIAL REQUIRED

2 EA. 2 LB./L.F. GALVANIZED FLANGED CHANNEL STEEL POST 6'-0" Long W/3" mounting holes at 1" centers and POINTED END.


 $\frac{5}{16}$ "×2" Galvanized carriage bolt with lock nut and nylon washer. 2 EA. MOUNTING BOLTS  $\frac{5}{16}$ "×1  $\frac{1}{4}$ " FOR SECURING THE 2 EA. SIGN POSTS. 2 EA.

ALTERNATE MATERIAL 2 LB./L.F. GALVANIZED FLANGED CHANNEL STEEL POST 1 EA. 8'-0" LONG W/3#8" MOUNTING HOLES AT 1" CENTERS AND POINTED END. 2 EA. 5#16"x2" GALVANIZED CARRIAGE BOLT WITH LOCK NUT AND NYLON WASHER.


DERAIL MARKER POST

NO SCALE

T-22





**ISSUED FOR BID** 




1) ARRANGEMENT IS SHOWN FOR INSTALLATION USING STEEL CROSSTIES WITH POSITIVE RESTRAINT RAIL FASTENING SYSTEM FOR APPLICATION IN BALLASTED TRACK AND FOR FULL EMBEDMENT IN REINFORCED CONCRETE PAVEMENT SLAB. 2) ALTERNATE METHODS OR MATERIALS FOR CONSTRUCTING BALLASTED TRACK OR FOR SETTING ALIGNMENT AND GAUGE OF RAILS FOR INSTALLATION OF FULLY EMBEDDED TRACK MAY BE ACCEPTABLE SUBJECT TO PRIOR SUBMISSION TO, AND RECEIPT OF APPROVAL OF ENGINEER. 3) CONTRACTOR TO SUBMIT SHOP DRAWINGS FOR ARANGEMENT OF CONCRETE REINFORCING THRU ENTIRE TURNOUT TO ENGINEER FOR APPROVAL PRIOR TO INSTALLATION.

4) CONCRETE FOR ALL TRACK CONSTRUCTION SHALL HAVE MINIMUM COMPRESSIVE STRENGTH OF 5000 psi @ 28 DAYS.







'un inv


WN FST PROJ

**ISSUED FOR BID** 


CAMDEN, N.J. S.J.P.C. BALZANO MARINE TERMINAL


RAIL INFRASTRUCTURE REHABILITATION TRACK CONSTRUCTION DETAILS


> RAWING NUMBER T-24



DRAWING #USK-1136, SHEET LOF 4.







RFV	BY	DATE	D
	ויטן		

X:\2021500064.000 - SJPC Balzano Rail Rehab\Technical\Electrical\E-001.dwg


## NOTES:


1. ALL WORK ON THIS SHEET ASSOCIATED WITH ADD ALTERNATE #1.


Z


- 2. ALL WIRING IS DIAGRAMMATIC. EXACT DIMENSIONS, LENGTH OF CONDUIT RUNS, ETC TO BE DETERMINED IN FIELD.
- 3. LIGHT FIXTURE SPECIFIED (TOTAL OF 4) ARE LITHONIA CNYLEDP240KMVOLTDDBM4. THIS SPECIFIED LIGHT FIXTURE INCLUDES A QUICK-MOUNT MECHANISM FOR MOUNTING TO THE RECESSED JUNCTION BOX NOTED IN DETAIL B.
- 4. 1-1/2" RGS CONDUITS ARE TO BE RUN ON, AND ATTACHED TO, THE BOTTOM CHORDS OF EXISTING ROOF TRUSSES. IF ADDITIONAL INTERMEDIATE SUPPORT IS REQUIRED, IT IS TO BE IN ACCORDANCE WITH TABLE 344.30(B)(2) OF THE NEC, LATEST EDITION.
- 5. DISABLE POWER TO LIGHTS ON EXISTING FLAGPOLE. TURN OFF CKT. BKR. IN TRANSIT SHED NO. 2 & CUT WIRES AT WEATHERHEAD. FOR LOCATION OF FLAGPOLE, SEE DRAWING T-3. THE WIRING AT THE WEATHER HEAD SHOULD HAVE 12 " PIGTAILS THAT ARE CAPPED AND TAPED. IF THE REPLACEMENT LIGHT IS NOT ADDED IN A TIMELY MANNER, THEN THE CIRCUIT BREAKER SHOULD BE REMOVED, OR TAGGED WITH A NOTE STATING THAT IT SHOULD NOT BE MOVED TO THE CLOSED POSITION.
- 6. PROVIDE SIMILAR ELECTRICAL CONDUIT AT TWO NEW DOORS AND OVERHEAD LIGHT FIXTURES AT TRANSIT SHED 1.

					ISSUED FOR BID
			URBAN ^L	JRBAN Phi (215) 922-	ENGINEERS, INC. 530 Walnut Street ladelphia, PA 19106 -8080 Fax (215) 922-8082
	TOF NEW JEAN	LOCATION	CA	MDEN,	NJ
		TITLE	RAIL INFRASTF	RUCTURE	INE TERMINAL REHABILITATION LECTRICAL DETAILS
	Manager and				
_	~~~000000000	DWN FYC	PROJ # 2021500064.000		
		^{CHK} JJQ	DATE 06/24/2022		E-001












REV BY DATE DESCRIPT






REV	ΒY	DATE	

- h		
-		
7' EX 101110		
200'x0'-9" ADD 100 5 FLATE		
2/6 CUTSHORE		
318 CUTSHORE VARIES FROM 8% TO 10% * 14 SHORE		
DU JT. HOSE		
x 0'3/2"		
_		
פטסענאודע		
INC.		
RATION		
contract H-ICEO no. nev.		ISSUED FOR BID
	OF NEW ST	LOCATION URBAN ENGINEERS, INC. 530 Walnut Street Philadelphia, PA 19106 (215) 922-8080 Fax (215) 922-8082 CAMDEN, N.J.
	ON NO. FLOW CONTRACTOR	S.J.P.C. BALZANO MARINE TERMINAL RAIL INFRASTRUCTURE REHABILITATION BERTH 3 - BERTH 4 RAIL CONNECTIONS CONSTRUCTION RECORD DRAWINGS
		DWN FST PROJ# DRAWING NUMBER CHK DATE EX-1





REV	ΒY	DATE	